

SCIENTIFIC AMERICAN


[Entered at the Post Office of New York, N. Y., as Second Class Matter. Copyrighted, 1889, by Munn & Co.]

A WEEKLY JOURNAL OF PRACTICAL INFORMATION, ART, SCIENCE, MECHANICS, CHEMISTRY, AND MANUFACTURES.

Vol. I.XI.—No. 11.
ESTABLISHED 1845.

NEW YORK, SEPTEMBER 14, 1889.

\$3.00 A YEAR.
WEEKLY.



1. Longitudinal Section of Tunnel and Shafts. 2. Perspective and Plan showing Difference in Alignment in Shaft, East End of Siphon. 3. Building Inverted Arches, Shaft 25. 4. Pump, Aqueduct Shafts, and Blow-off; building Blow-off.

THE NEW CROTON AQUEDUCT TUNNEL UNDER THE HARLEM RIVER.—[See page 165.]

Scientific American.

ESTABLISHED 1845.

MUNN & CO., Editors and Proprietors.

PUBLISHED WEEKLY AT

No. 361 BROADWAY, NEW YORK.

O. D. MUNN.

A. E. BEACH.

TERMS FOR THE SCIENTIFIC AMERICAN.

One copy, one year, for the U. S. or Canada.....\$3 00
 One copy, six months, for the U. S. or Canada..... 1 50
 One copy, one year, to any foreign country belonging to Postal Union, 4 00
 Remit by postal or express money order.

Australia and New Zealand.—Those who desire to receive the SCIENTIFIC AMERICAN, for a little over one year, may remit £1 in current Colonial bank notes. Address

MUNN & CO., 361 Broadway, corner of Franklin Street, New York.

The Scientific American Supplement

is a distinct paper from the SCIENTIFIC AMERICAN. THE SUPPLEMENT is issued weekly. Every number contains 16 octavo pages, uniform in size with SCIENTIFIC AMERICAN. Terms of subscription for SUPPLEMENT, \$5.00 a year, for U. S. and Canada. \$6.00 a year to foreign countries belonging to the Postal Union. Single copies, 10 cents. Sold by all newsdealers throughout the country.

Combined Rates.—The SCIENTIFIC AMERICAN and SUPPLEMENT will be sent for one year, to any address in U. S. or Canada, on receipt of seven dollars.

The safest way to remit is by draft, postal order, express money order, or registered letter.

Australia and New Zealand.—The SCIENTIFIC AMERICAN and SUPPLEMENT will be sent for a little over one year on receipt of £2 current Colonial bank notes.

Address MUNN & CO., 361 Broadway, corner of Franklin Street, New York.

NEW YORK, SATURDAY, SEPTEMBER 14, 1889.

Contents.

(Illustrated articles are marked with an asterisk.)

Aluminum.....	167	Inventions, mechanical.....	170
Am. Ass. Ad. Sci.....	164	Inventions, miscellaneous.....	170
Am. Geolog. Soc., meeting.....	168	Lamp, arc, Carson's.....	164
Arches, inverted, building.....	159	Lamp, car, electric.....	169
Baths, free, Milwaukee.....	168	Lock, switch, Caine's.....	163
Boat, jet, Evolution.....	160	Mahogany, Mexican.....	167
Business and personal.....	170	Meeting, A. A. S., Toronto.....	160
Can, oil, Rau's.....	163	Notes and queries.....	170
Car, dumping, Gearhart's.....	162	Notes, photographic.....	165
Cart, road, Doolittle's.....	162	Patents, Thos. A. Edison.....	165
Cock, blow-off, Mitchell's.....	162	Philadelphia, launch of.....	164
Convention, photo., in London.....	164	Porpoise, the.....	169
Cotton manuf. in Brazil.....	161	Pump, aqueduct shafts, etc.....	159
Current, alternating, deadly.....	166	Rheostat and resistance column.....	163
Deafness in old age, relief.....	168	Sewage disposal problem.....	161
Discoveries, Egyptian.....	161	Sugar, beet, progress of.....	169
Edison, with, on Eiffel Tower.....	166	Sugar for boiler incrustations.....	165
Exhibition, Paris.....	169	Tank, roofing, Burkelman's.....	162
Eyepiece, astigmatic—correction.....	165	Textiles, incombustible.....	165
Force, electric, in derrick.....	162	Transparencies, albumen.....	161
Gas, natural, for balloons.....	165	Tuna, Mexican.....	161
Gate for drawbridges, King's.....	162	Tunnel, Harlem River.....	159, 165
House, dwelling, cheap.....	167	Tunnel, Harlem River, perspective.....	159
Insurance, life.....	167	Tunnel, Harlem River, section.....	159
Inventions, agricultural.....	170	Wages, continental.....	167
Inventions, engineering.....	170	Wasp, spider-hunting.....	161
Inventions, index of.....	171		

TABLE OF CONTENTS OF SCIENTIFIC AMERICAN SUPPLEMENT No. 715.

For the Week Ending September 14, 1889.

Price 10 cents. For sale by all newsdealers.

I. ASTRONOMY.—A Portable Sun Dial.—A simple sun dial determining the time by the altitude of the sun irrespective of the points of the compass.—1 illustration.....	11424
II. BIOGRAPHY.—Elias Loomis, the Physicist.—By H. C. HOVEY.—An interesting note of the life and achievements of the eminent astronomer and meteorologist.....	11422
III. CIVIL ENGINEERING.—The Manchester Ship Canal.—The famous Manchester canal now approaching completion, the probabilities of its future traffic, the docks in connection with it, and general notes of the progress of the work.—2 illustrations.....	11415
IV. MECHANICAL ENGINEERING.—On Gas Engines.—By EDWARD DELAMARE-DEBOUTTEVILLE.—Commencement of an elaborate paper upon the history and progress of this line of invention, with description of different devices.—15 illustrations.....	11416
Recent Improvements in the Pulsometer.—Description of six new pulsometers of various construction, with illustrations of the same in section or elevation.—9 illustrations.....	11418
Wire Straightening Machine.—A wire straightening machine utilizing pulleys instead of dies for the purpose, avoiding the wearing out of dies and the injury of the wire.—1 illustration.....	11418
V. METALLURGY.—Process of Preventing the Oxidation of Metals while in a Heated Condition.—By GEORGE WYCKOFF CUMMINS and JAMES HENRY COLEMAN.—A process for heating iron or steel without injuring it by oxidation, preventing scaling of the surface and other deteriorating effects.—1 illustration.....	11425
VI. METEOROLOGY.—Luminous Night Clouds.—An appeal from the Berlin Observatory for volunteer observations of luminous night clouds, which for the last few years have appeared during the months of June and July.....	11425
VII. MILITARY TACTICS.—Military Velocipede in France.—Proposed use of the bicycle in war.—An article of much interest at the present day, describing the experiments now in progress in France.....	11421
VIII. NAVAL ENGINEERING.—Armor Plate.—The conclusion of this elaborate article, giving the further results attained with armor plates of different manufactures under impact of heavy artillery.—13 illustrations.....	11419
IX. PHYSICS.—Thermometers.—By FRANK BROWNE.—An elaborate paper on the subject of the manufacture of thermometers, their uses, the different scales, their calibration and sources of error.—2 illustrations.....	11422
X. STATISTICS.—The United States—Their Growth in Population in Two Hundred Years.—A very interesting note of the increased population of the United States, and the prediction of its future extent 100 years from now.....	11425
XI. TECHNOLOGY.—On the Purification of Alcohol by Means of Hydrocarbons.—By W. S. SQUIRE, Ph.D.—An exhaustive paper on this important subject in technology, disclosing a method of purifying alcohol by the use of hydrocarbon oil.—6 illustrations.....	11428
The Ageing of Logwood.—An important article for the dyer upon the importance for his uses of the age of logwood and influence of time upon its dyeing properties.....	11424

THE NEW JET BOAT EVOLUTION.

A few weeks ago we gave an account of the new experimental 100 ft. boat Evolution, which is to be propelled by a high pressure water jet, and from which greatly improved results are expected by Dr. Jackson, the projector, and his friends. The propulsion of boats by expelling a jet of water from the stern is a very old idea and has often been tried, but heretofore with loss of speed as compared with the ordinary screw or wheel propeller. In all of these jet experiments, a large jet of water has been used at a comparatively low velocity. Jets varying from 5½ feet area to 7½ inches have been used.

In this new boat, the Evolution, now nearly ready for trial in this harbor, the propelling jet of water is to be only three-fourths of an inch in diameter, delivered under the enormous pressure of 2,500 pounds to the inch. This is a novel and striking departure from the old methods. The builders confidently expect the new system will revolutionize the art of steam navigation and render useless the employment of the present cumbersome forms of marine engines, propelling screws and wheels. That a tiny stream at high pressure should be more effective in propelling boats than a large stream at low pressure is generally denied by the best engineering authorities. The new boat has been constructed to work in almost direct contradiction to the theories and calculations of Rankin and other naval scientists.

The following, by Mr. S. Alfred Varley, may perhaps be regarded as an explanation of the scientific basis upon which the new enterprise rests.

"In the transmission of energy hydraulically, there is a loss of useful energy arising out of the fact that the energy has to move the vehicle of its transmission bodily, and this general law would seem to prevail in all cases, viz., the higher the potential, *i. e.*, the greater the amount of energy to the weight of its vehicle, the more complete is the transmission.

"As an example of what seems to be a general law, consider the transmission of energy mechanically by means of a long wire passing over pulleys and moved rapidly in alternate directions; the overcoming the inertia of the wire and the pulleys, and the friction encountered, will consume energy. Let it be assumed the waste from the above causes equals 50 per cent of the energy, if the wire and the pulleys can be reduced to half their weight, the inertia and the friction will be correspondingly reduced, and 75 per cent, instead of 50 per cent, would be transmitted.

"The same general principle to that above mentioned, in reference to the transmission of energy by means of a wire, holds good with hydraulic transmission, and also with steam engines.

"When energy is transmitted to a distance hydraulically, the greater the amount of energy associated with the water moved, in other words, the higher the potential or pressure employed, the greater the percentage of energy transmitted and developed as work at the distant station."

THE SCIENTIFIC MEETING AT TORONTO.

The American Association for the Advancement of Science proves its continental character by occasionally crossing the line into Canada, and whenever it does so, it is sure of a hearty greeting. Nowhere has this important society met with a more cordial welcome. Toronto has 180,000 inhabitants, every one of whom believes the Behring Sea to be an open sea and the British flag to be the most glorious of all national emblems. And yet at the grand reception given to their guests, August 28, at the Pavilion in the Horticultural Grounds, they found a number of star-spangled banners, which they alternated with their own with beautiful effect. This was all the more appropriate because every State in the Union and every Province in the Dominion was represented in this scientific congress. It may be added that many of the master minds of the age were in attendance.

Conspicuous on the platform were seven individuals who had been honored as presidents of the Association, namely, Professors Dana, Hall, Barker, Newton, Dawson, Morse, and Mendenhall. In the absence of the retiring president, Major Powell, whose duties in connection with the reclamation of arid lands detained him, the chair was taken by the venerable Prof. Dana, who, after brief remarks, surrendered it to the president-elect, Prof. Mendenhall, recently of the Rose Polytechnic Institute of Terre Haute, but now at the head of the United States Coast Survey.

The Association was formally welcomed to Toronto by the mayor of the city, the Minister of Education, the Chancellor of the University, and other dignitaries. To these the chairman replied. Of course these speakers could hardly avoid making some reference, mostly in a humorous vein, to the existing complications between the two adjacent countries.

But Prof. C. S. Hill, vice-president of the section of economics and statistics, made quite a sensation by his opening speech on the "Relations of the Canadian States and the United States." He thought it remarkable that the former people should not unanimously desire annexation to such a progressive and en-

terprising people as ourselves. There can be but three Americas—north, central, and south; and eventually there will be but one people from the Atlantic to the Gulf, bound by inseparable ties of language and consanguinity. He denounced strongly the policy of free trade as long as Canada remained a part of the British empire, and contrasted the bitter racial and religious antipathies existing under a cold monarchical sway with the obliteration of such rivalries in a republic. And so he went on to prove conclusively that "there is no future for Canada but in union with the United States, which is to-day the first in industry, education, and wealth among the nations of the world"—all of which is doubtless true enough, but of a nature to provoke sharp criticism from the Toronto press.

The other opening addresses before the several sections were on less exciting topics. Prof. Woodward addressed the section including mathematics and astronomy on the "Mathematical Theories of the Earth," as to its shape, size, constitution, distribution, of its mass, internal heat and secular cooling, crust movements, and sundry theories of cosmogony. Prof. Carhart, before the section of physics, reviewed the "Theories of Electrical Action." Electrical applications increased so rapidly that only experts could keep pace with them, although they awoke universal popular interest. He expressed the hope that electricity and magnetism might yet be obtained from sunlight. He gave a retrospective view of work done by electricians during 225 years, most of which period was barren. Maxwell's translation of Faraday's ideas into mathematical language, 16 years ago, marked an epoch. Nothing further seems to be necessary to prove the electro-magnetic theory of light than the astounding facts that electro-magnetic waves are reflected from the walls of a room, and that an iron post casts an electro-dynamic shadow. Electricity annexes the domain of light and radiant heat. Henceforth, luminiferous ether must always have place in language describing electrical phenomena.

In the section of anthropology, the opening address by Vice-President Garrick Mallery was an effort to show a strong similarity between the Israelite and Indian races. He discussed their ideas of religion and planes of culture, announcing the fact that revelation, which is usually claimed as antedating religion, is the last step in its evolution, being the point where the mind clings to faith as a final refuge from doubt, that is for so many the synonym for despair.

In the chemical section, Prof. Dudley, of Nashville, discussed "Amalgams." His paper was highly technical. He asserted that work done hitherto on amalgams was very desultory, zealous investigations being usually cut short with lame results, whereas it is vitally important for us to continue our own lines, as well as those begun by others, to legitimate conclusions.

"Protoplasm, or Living Matter," was the theme on which Prof. G. L. Goodale opened the biological section. He said that the term protoplasm was familiar to all. He reviewed the history of researches as to cellular tissue from 1667 down to the present time. Cohn and Unger have shown that the protoplasm of vegetable cells was identical with what had been already observed in animal structure. Recent observers have made fresh examinations throwing light on the mechanism of its movement and its mysterious power of spontaneous motion.

The address before the section of geology and geography, by Prof. C. A. White, was on the North American Mesozoic, a subject he has made his special study. The rocks occur along the Atlantic and Pacific coasts as well as in the interior, and rest unconformably upon various formations. The Atlantic Mesozoic consists of a representation of the Upper Trias of Europe, the Upper Jura, and Middle and Upper Cretaceous.

The Mesozoic rocks are so widely separated that, as we go westward by way of the Gulf States, we find none till we face the 100th meridian. No Triassic rocks exist within the 30,000 square miles of Texas and the Indian Territory which some geologists say are wholly occupied by such rocks. The "red beds" upturned against the Rocky Mountains, which by common consent have been referred to the Trias, and are several thousand feet thick, are non-marine and as a rule barren of fossils. The evidence is meager to prove their Triassic age. The break between that age and the Paleozoic of North America occurred while the living forms of the latter were far in excess of the former. Hence the Mesozoic limit must coincide with the earlier or later Trias. We are unable to designate closely its upper limit in the interior and Pacific regions, but in the Atlantic coast region it is where the marine Eocene rests on the Upper Cretaceous. The speaker in conclusion advanced certain propositions which involve the common methods of paleontologists, who assume to be able to determine precisely the age of any and all fossils without reference to stratigraphy, and who also use European classification as if it were of infallible application to all other parts of the world. The formations of any given continent ought to be first investigated with relation to each other, and afterward in correlation with those of other continents.

Major J. W. Powell's address as the retiring president (read in his absence by Prof. Gilbert) was heard by a vast audience convened in the Pavilion. It was on the "Evolution of Music—from the Dance to the Symphony." It was an hour and three-quarters long, and abounded in learning, wit, and poetry. Indeed, the remark was made by one of his illustrious predecessors, in whose footsteps he did *not* tread, that the address would have been more suitable for an association for the advancement of poetry than of science. Among the things said by Major Powell were these: The laws of biotic evolution do not apply to man. Human classification is by culture, and culture is the product of endeavor. Of this the evolution of music is an illustration. In it there is no survival of the fittest, for many a screaming soprano holds her own in opera, and many a wretched fiddler ranks as first violin in orchestra. No adaptation to environment, for many a choice musician comes from families where music is lightly prized, while thousands of dollars are vainly lavished on those that "have no ear." A Jenny Lind or a Nilsson will sing as sweetly in Louisiana as in Sweden.

The fact is that music is the invention of mankind. There are four germs for the four fine arts. Fetish carving is the germ of statuary; tattooing of painting; mythology of the drama; and the dance of music. All art is symbolic. How did music grow? The rhythm of motion became the rhythm of emotion. The rock-leaved bible of geology tells us of the sylvan man who moved in figures of harmony while his voice kept time. Then came stress. Then pitch. The egg of poetry was laid, and of melody; for they were both born of the dance chant. At last the child is emancipated, and music is no more chained to terpsichorean feet. Savages see mystery everywhere and people earth, air, and sea with gods, whose acts are presented in the drama. Even in civilized lands the highest and best men ponder the problems of creation; and the mythic dramas of savage life become the oratorios of the Christian. Harmony is the combination of melodies; and symphony is a sequence of harmonies. Science comes to make music sublime. Instruments are made that go beyond the limits of the voice and thus enrich all occasions.

From the primitive fire-light dance come the folk-songs, cradle-songs, love-songs, war-songs, songs of patriotism and songs of Christian hope. Music thus comes to be the language of the soul as stirred by the glories of the universe. Is there a new music of the future? Science says yes. We know that music has been chained to form and imprisoned in the Bastille of musical intervals and guarded by the henchmen of dogmas. But a few great composers, like Wagner, have broken the chains, and burst the bars and killed the gaolers, and they sing their liberty in strains of transcendent music.

THE SEWAGE DISPOSAL PROBLEM.

As cities increase in size, the problem of sewage disposal becomes a more and more difficult one to solve. The English sanitary engineers, with a densely populated country, including the largest city in the world, as a field for experiment, have probably performed more experiments on an actual working scale than have those of any other nation. Chemical treatment has been tried in an endless variety of forms. The A B C process, named from the initials of the substances used in carrying it out, alum, blood, and charcoal, at one time had an extensive application. Now the tendency is toward the use of chemical salts alone, aluminum, iron, and calcium compounds being most in favor. Precipitation is assisted by the addition of comparatively small amounts of these salts, perchloride of iron, alum, milk of lime, and others being in use in various places. After treatment with chemicals, the sewage is left at rest to deposit its solid matter. The effort is to obtain the latter in as compact a form of "sludge" as possible, and during its precipitation to deodorize the liquid portion, so that it may be disposed of without offense.

The engineers interested in this problem seem to have had very Utopian ideals. Their object has been to dispose of sewage without offense and at the same time profitably. The first of these ends is easy of attainment, the latter is probably impossible to achieve. The great problem is how to separate liquid and solid. This once done, the solid can be desiccated and disposed of as easily as ashes or any other form of refuse. The liquid can be used for irrigation.

Where chemicals are not used, the separation can be effected mechanically. Upward and downward filtration may be used in connection with and supplementary to settling in subsidence tanks. The trouble in purely mechanical treatment is the odor of the effluent water. A proper and sufficiently thorough application of chemicals only can remove the odor. The necessity of perfect deodorization is most felt in the case of towns and cities in the interior. Dilution is a great panacea for this trouble, but is only practical near large bodies of water. Inland cities have to produce as clear and innocuous a filtrate as possible. Mechanical filtration alone will not effect the desired result.

In England the disposal of the effluent from filtration or precipitation is conducted by irrigation to a very large extent. On the Continent the same system has been adopted, notably in the case of the city of Berlin. Overground irrigation upon plowed fields seems to be very effectual. In this country subsoil irrigation is used in an immense number of localities, principally by private houses and hotels, and meets with excellent success.

The sludge or solid matter remains to be got rid of. The constant effort to make sewage farms profitable and to make sewage a source of revenue to the corporations of cities producing or disposing of it, has to a certain extent caused an erroneous view to be taken of the matter. The conclusion is gradually forming in the minds of engineers that sewage sludge is of little value. The hopes so long entertained of putting it into a marketable form, so that it would be in demand as a fertilizer, seem doomed to disappointment. From many places the same story comes; that sewage works are a source of expense, and that the sludge, fortunately very small in amount, is of practically very little or no value. In London the same attempt has been made to profitably dispose of the solid matter, but it has had no success. It was collected and pressed into blocks at a cost of 4s. 6d. a ton. In this form it could not be sold at even a nominal price. Farmers would have none of it. Pressing was abandoned, and some of it is now delivered in the wet state as compactly as possible into tank steamers. In this way some three thousand tons a week are carried beyond the Nore and are deposited in the German Ocean. The cost is put at 6d. per ton. This is by no means all of the solid matter of the London sewage. A great quantity still goes into the Thames, polluting its waters. In the case of a vessel that went down in the river below London, some years ago, it was related that the death of some of the passengers was caused by the poisonous exhalations from the water rather than by simple drowning.

Sludge from a chemical precipitation works in the neighborhood of this city was recently tried upon a farm in comparison with ordinary manure. The conclusion reached was that it was of more harm than good, and that the land without manure did better than that which received sludge alone.

This, then, may be said to be the present aspect of the sewage problem. Money must be spent to get rid of it. The efforts of engineers should be in the direction of economical disinfection and deodorization; profit should be out of the question. The problem is one of growing importance. If the facts above outlined are realized, the problem will be more effectually grappled with than where the idea of sewage having a monetary value prevails.

The Mexican Tuna.

In the *West American Scientist* Mr. Edward Palmer writes entertainingly of the fruit of the opuntia, or *tuna*, as it is called in Mexico, where it forms the principal article of food for many of the natives during several months of the year. The tuna of the Mexicans must not be confounded with the opuntias found in southern California and Arizona. Many valuable varieties of opuntia are found growing in the cactus belt of Mexico, and seeds of some of the most desirable were furnished originally by the United States Department of Agriculture. When new varieties are produced by artificial crossing and selection, as great improvement may be expected as has been made with other cultivated fruits, but the different varieties now have no distinctive names. This cactus requires little care, and thrives on almost any soil, but it reaches its best condition on the table lands of Mexico. A piece of the plant laid on the surface of the ground will take root and grow; it will endure considerable cold, and the most protracted drought only seems to increase the sweetness of the fruit. When gathered, the fine spines on the surface of the fruit must be removed, so that it can be handled without inconvenience. The skin is then removed, leaving the pulpy meat exposed in a most tempting manner. It is specially adapted to the breakfast table, having something of the watermelon flavor, with a suggestion of strawberry. Tuna is abundant and cheap in the market from June till November. It is finding its way along the frontier of the United States, and is already on sale in Jacksonville and other Southern cities.—*Garden and Forest*.

Egyptian Discoveries.

Before the Victoria Institute M. Naville recently gave an account of his latest Egyptian discoveries. The lecturer gave a description of his discovery of Bubastis, where he unearthed numerous inscriptions dating back to the Fourth Dynasty, among others some referring to Cheops, showing that he reigned over all Egypt, some to the invasion of the shepherds or hyksos, who, from some of their monuments found, were clearly highly cultivated, and came from Mesopotamia. Among their statues unearthed were two of Apepi, the Pharaoh of Joseph, also inscriptions in regard to the Pharaoh of the Exodus, and others of high interest.

Albumen Transparencies.

Transparencies by the albumen process are still unsurpassed by those of any other, and it is in this direction that the process has mainly been employed since the introduction of collodion. The famous stereoscopic slides of the late M. Ferrier, made more than thirty years ago, are as good as, if not better than, any that are made now, notwithstanding all the modern improvements in photography. Indeed, even now, albumen transparencies are looked upon as the standard of perfection, for it is seldom that more is claimed for any process than that "it is nearly, or quite, as good as albumen"—never that it is superior.

A glass plate, after being carefully cleaned, is coated with iodized collodion of a somewhat porous or rotten character. It is then washed in water to remove the ether, alcohol, and iodide. After draining, the iodized albumen is poured on and allowed to soak well into the film. The plate is then reared on end to dry. By the way, all these operations may be conducted in open daylight. The collodion, it may be mentioned, acts purely mechanically, and takes no part in the formation of the image. The plate, when dry, is sensitized in a silver bath, strongly acidified with acetic acid. Forty-five grains of nitrate of silver and forty-five minims of acetic acid to the ounce of water are the proportions usually adopted. The plate is then washed and again dried. The exposure is generally made by contact printing. In the earlier days of the process the development was by means of gallic acid, but the more modern method is with acid "pyro," used warm. After fixing in hyposulphite of soda the image is toned with gold to the color desired.

The principal charm in albumen transparencies is the extreme brilliancy and transparency of the shadows.—*British Journal of Photography*.

A Spider-hunting Wasp.*

Not long since, while I was enjoying a siesta on the porch, my attention was suddenly attracted by seeing a very large spider running up the body of a tree about ten feet away. The spider seemed to be very much excited, and, after he had run up the body of the tree about six feet, he ran out on a side limb, and, after he had gone about eight feet out on this limb, he dropped off to the ground. No sooner had he struck the ground than he commenced a headlong flight through the grass of the lawn. After he had run about five feet on the ground, I saw a very large wasp, about two inches long, following the track of the spider on the tree. The wasp was running and flapping his wings in a nervous manner, but was not flying at all. In a few minutes the wasp arrived at the spot where the spider had dropped off, which, by the way, was about ten feet from the ground. Here the wasp became very much excited, and ran rapidly back and forth about a minute. Then he took flight, flew to the root of the tree, where I saw him at first, and ran up the track again. Soon he arrived at the jumping-off place, and again became very excited, running round and round, and flapping his wings nervously. Suddenly the wasp stopped, and appeared to be *thinking*. Certainly his actions bore out this conclusion, for he closed his wings and dropped off the limb, just where the spider had dropped. Arriving at the ground, he recommenced the search, and, after a few futile attempts, he struck the scent, and away he went, just exactly as a hound would have followed a deer. After running about ten feet on the ground, he overtook his prey.

The spider either saw or heard his enemy coming, for, without waiting to be overtaken, he threw himself upon his back, with his feet in the air, and in this posture awaited the attack. The wasp lost no time in beginning, but, to my surprise, seemed to be somewhat afraid of the spider. The wasp took to his wings, and would fly round and round the spider, and would now and then make a sudden thrust at him. The spider would, at these times, jump forward and seemed to be trying to catch the wasp. The wasp was too agile, however, to be caught. Suddenly the wasp made an attack, stung the spider, and in less than half a second the spider was perfectly dead. Electricity could not have killed him quicker. The wasp, after satisfying himself that his prey was dead, sat on the grass near by and proceeded to rest himself, for his violent efforts had exhausted him. After resting about two minutes he approached the spider, and, after examining him critically with his antennae, straddled him, and proceeded to bear him away.

Just here I put in a say-so, and captured wasp and spider, and immolated both to my scientific curiosity. This occurrence would seem to show that the wasp can track by smell, and can likewise *reason*, else why did he drop from the limb? I regret to say that I neglected to keep the spider and observe whether he had been really killed, or only put into the lethargic condition into which our dirt daubers put their spiders.

I am not versed in entomology sufficiently to give the technical names of either wasp or spider. The spider was very large, his abdomen being about half an inch long.

* By L. S. Frierson, Frierson's Mill, La., in *Popular Science News*.

AN IMPROVED ROAD CART.

A two-wheeled vehicle designed to greatly lessen the disagreeable joggling motion ordinarily imparted by the movement of the horse is illustrated herewith, and has been patented by Mr. E. W. Doolittle.




DOOLITTLE'S ROAD CART.

little, of Garden Grove, Iowa. By this invention short shafts, secured to the axle and supporting the seat, are pivotally connected with long shafts, springs being interposed between the long and the short shafts, and the lugs by which the pivotal connection is made have different apertures for changing the pivotal point to regulate the pressure on the springs. The latter are attached to the short shafts just back of the ends of the long shafts, on the ends of which they bear and are held in place by a hook-like iron strap. To a transverse beam connecting the ends of the short shafts are similar springs, which are connected at their other ends with the bent bars that support the platform or foot rest, these bars at the rear of the platform being bent upward and then rearward, where they carry the seat. The latter is slotted, and attached by bolt with thumbscrews, to allow for shifting it forward or backward as desired. The rear of the platform or foot rest is hung from the short shaft by means of a coil spring, such attachment being adjustable in different positions on the shaft by means of a ring bolt and thumb-screw, whereby the position of the spring may be changed according to the weight carried. The principle of this invention is also intended to be applied with a pole as well as with shafts.

AN IMPROVED DUMPING CAR.

A car arranged to be dumped from the engine, by means of compressed air or steam, is illustrated herewith, and has been patented by Mr. Joel H. Gearhart, of Leadville, Col. The car body is hinged to the platform or truck, and beneath the platform, to one side of the center, is mounted a vertical cylinder in which works a piston having an outwardly extending stem to which there is hinged a connecting rod or link, the outer end of this link being hinged to the car body. In connection with the cylinder are arranged two systems of pipes, a pipe from one system entering the cylinder above the piston and one from the other system entering the cylinder below the piston, and these systems are connected with a compressed air reservoir carried by the locomotive, or with the steam supply. In the two systems are arranged valves, preferably such as employed with the Westinghouse automatic brake, whereby, on the admission of steam or compressed air to the bottom of the cylinder, the piston will be raised



GEARHART'S DUMPING CAR.


to tip the car body, as shown in the illustration, the car body being returned to its normal position by the admission of steam or compressed air to the top of the cylinder. Couplings are provided whereby any number of cars may be connected in such a system, and the engineer can dump the cars and return them to normal position while the train is in motion as well as when it is at rest.

Electric Force in a Derrick.

The *Progressive Age* relates an amusing exhibition of the magnetic force of electricity as given in Lynn, Mass., when seven workmen tried to remove a derrick against which an electric light wire was sagging. They grasped one of the guys and were unable to remove their hands. The foreman berated his workmen in the good old country fashion. He had never had experience with electricity before, and was at a loss to comprehend what had so suddenly bewitched his men. Every one of them was hanging to the guy rope with the energy of desperation, yet powerless to move it. The foreman grasped a guy, and then the real state of the case came home to him. He, too, was transfixed. The electric current found him an excellent conductor, and ran down through him into mother earth. The affair, which had been very amusing, was fast getting serious, when the connection was as suddenly broken. The guy, which had made all the trouble, dropped away from the electric wires and the men were released. No serious consequences ensued.

AN IMPROVED DRAWBRIDGE GATE.

The accompanying illustration represents a drawbridge gate which will close automatically upon the opening of the draw and will be raised to open the way across the bridge when the draw closes. This invention has been patented by Mr. Charles King, of New London, Ohio. To the under side of each end of the draw is secured a projection, which extends beneath the abutment, and upon the abutment, in suitable bearings, is mounted a rock shaft. This rock shaft is provided with a standard, to which there is rigidly connected a bar or gate frame, adapted to form a barrier, there being also connected to the rock shaft a downwardly extending curved lever, which extends into the path of the projection from the draw. When the draw is closed and the bridge open to travel, as shown in full lines in the sectional view, the projection from the draw is in engagement with the curved lever to hold the barrier or gate frame in raised position; but on the opening of the draw the projection rides from beneath




KING'S BRIDGE GATE FOR DRAWBRIDGES.

the lever, and the weight of the bridge bar or barrier carries it down to the position shown in dotted lines, to close the bridge to travel. A prop is provided on which the extended end of the bar or barrier rests when in position across the roadway, such a gate being arranged in connection with each end of the draw.

AN IMPROVED BLOW-OFF COCK AND FIRE EXTINGUISHER.

A device to be used on locomotives for cleaning the boiler, and at the same time serving to sprinkle wooden structures in the track, such as bridges, ties, trestles, etc., to prevent their being set on fire, is illustrated herewith, and has been patented by Mr. Lucius E. Michell, of Palestine, Texas. The device, shown in section in Fig. 1, is preferably secured to the lower part of the front end plate of the boiler, and has a valve body provided on its inner end with a valve seat leading to a longitudinal central opening. An inwardly opening valve is held on the seat, and has wings extending inward into the central opening, the inner ends of the wings being connected with a central valve stem, carrying a piston sliding in the central opening. The outer end of the piston rod is pivotally connected with an arm secured on a shaft mounted to turn in suitable bearings on the front plate, as shown at 2 in the main figure. On this shaft is also an upwardly extending lever carrying near its handle end a catch adapted to engage a notch formed in a segment projecting from the front plate of the boiler. In the valve body is an annular chamber connected at its bottom with a hollow offset, from the ends of which extend pipes in opposite directions across the lower part of the front end

plate of the boiler, these pipes having downwardly opening apertures. The arrangement of the valve is such that by moving its lever into one of the notches in the segment, the water and steam from the boiler pass into the transverse pipes and are thrown down on




MICHELL'S BLOW-OFF COCK AND FIRE EXTINGUISHER.

to the track over which the locomotive is passing, as shown in the illustration, while by moving the lever to another notch, when it is desired to use the device as a blow-off cock, the larger part of the water and mud will pass out through the front open end of the valve body. For further information as to this invention address Messrs. Geo. M. Dilley & Son, Palestine, Texas.

AN IMPROVED ROOFING TANK APPARATUS.

An apparatus especially designed for transporting tanks or kettles for melting tar or other substances employed in roofing or sheathing buildings is illustrated herewith, and has been patented by Mr. Charles Burkelman, of No. 32 Sullivan Street, New York City. The apparatus includes a main four-wheeled truck, with its rear axle bent downward at the center to permit of the entry of a tank or kettle, for which there is an opening made in the rear part of the truck platform, there being a removable tail board to be applied after the tank is in place on the truck. The tank is supported at the place of use by a detachable truck, the bed of which has a general triangular form, and is sustained on a skeleton frame by two wheels at the front, and at the rear by a pilot wheel journaled in a bearing swiveled to a bracket bolted to the narrow end of the triangular frame. The bed is made of metal plates turned upward and inward at their ends to form hooks adapted to receive a flange formed at the bottom of the tank. The main truck is to be backed on to or around the detachable truck containing the tank, the main truck platform being cut away at each side of the opening

to permit of its easy entrance. Four separate planks are provided to close this opening, and form a continuous platform, so that the truck can be used for general work when desired, these planks being also used as a re-enforce to the main truck platform to help sustain the tank in position for transportation, the tank having near its top opposite side flanges which rest on top of the planks. To lift the main truck platform and tank, when the latter is to be moved, the truck axle is utilized as a resistance piece or bar. Screws with threaded nuts are secured to the platform over the rear axle, and are stepped in recesses of metal foot blocks shackled to the horizontal end parts of the axle, these screws being preferably operated from either side of the truck by chain wheels in connection with a transverse shaft



BURKELMAN'S PORTABLE ROOFING TANK APPARATUS.

sustained in bracket bearings bolted to the truck platform. Both ends of the transverse shaft are squared to receive the eye of a crank for turning the shaft and operating the screws to raise or lower the truck platform. The screws will ordinarily be turned to lift the platform and tank from three to five inches, or sufficient to take up the depression of the truck springs from the weight of the tank, when the detachable truck may be rolled out from under the tank and placed on the main truck.

RHEOSTAT AND RESISTANCE COLUMN.*

Besides the carefully constructed resistance boxes used in making electrical measurements, the electrician




Fig. 1.—GERMAN SILVER RHEOSTAT.

requires adjustable resistances for heavy and light currents, which need be only approximately accurate. These instruments are also a necessity to the electroplater and to users of dynamos and batteries generally.

Fig. 1 illustrates a simple rheostat for heavy currents. It is designed to be introduced into the field magnet circuit or the external circuit as circumstances may require.

This rheostat consists of a series of German silver spirals arranged in a circle, beginning at *b* and ending at *c*. The lower end of the first coil is connected with the upper end of the second, the lower end of the second is connected with the upper end of the third, and so on throughout the series.

On the top of the wooden frame which supports the spirals is arranged a switch formed of a series of brass or copper blocks arranged in a circle and separated from each other by a space, and a swinging arm pivoted at the center of the box and carrying at its free end contact springs adapted to press upon the blocks.

The block, *a*, is isolated from the other parts of the rheostat, and serves as a rest for the switch arm when the circuit is open. The block, *b*, is connected electrically with upper end of the first coil, and the next block is connected with the top of the second coil, and through the straight wire with the lower end of the first coil. The spirals are all connected in this way.

The rear binding post is connected with the pivot of




Fig. 2.—RESISTANCE COLUMN.

the switch arm, as indicated by the dotted line, and the one at the front of the frame is connected with the block, *b*.

When the switch arm is on the block, *a*, the circuit is broken; when it is on the block, *b*, the current passes from the farther binding post to the switch arm, thence through the block, *b*, directly to the first binding post without passing through any of the coils. When the switch arm is placed on the next block, the current passes downward through the wire connected with the lower end of the first coil, then upward through the coil to the block, *b*, thence to the binding post.

By moving the switch arm forward, the contact

springs carried thereby are made to touch one block after another, thus introducing more resistance with each additional coil included in the circuit.

The first coil thrown into the circuit should be of heavy wire, say No. 14 or No. 16, and the second, third, and fourth should be somewhat smaller. The wire of the entire series of coils might be graduated to advantage if the various sizes required are available.

The resistance of German silver wire is about ten times that of copper. If German silver wire cannot be conveniently procured, iron wire may be substituted. In this case the coils will have to be longer.

Eisenlohr's column of resistance, shown in Fig. 2, is inexpensive and very convenient. It consists of a cylinder of mahogany or other compact wood, having six or more grooves cut in it. The cylinder is saturated with paraffine or varnished with shellac, and the spaces between the grooves are bound with brass bands. A little brass bar, turning on a screw, is made to extend from one ring to the other, as shown. These bars are slightly bent so as to press with some force upon the bands. Covered wire of a known resistance is wound in these grooves, the shortest length containing the given unit once or an even number of times.


The length of the coils of wire in the successive grooves increases from 1 to 6; the ends of each wire are soldered to the two nearest bands, the upper band being connected with the screw, *a*, and the lowest with *b*. When this column is inserted in a circuit, the current passes from one ring to another through the bars, whose resistance is inconsiderable, but when one of the bars is turned aside, as shown in the engraving, the current passes through the intervening coil.

Coils of approximately 1, 2, 3, 6, 12, and 24 ohms resistance may be made by winding copper wire of the sizes and lengths given in the successive grooves as follows:

Ohms.	Ft.		Ohms.	Ft.	
1.....	37½	No. 24 Am. W. G.	6.....	56	No. 30 Am. W. G.
2.....	75	No. 24 " "	12.....	70½	No. 32 " "
3.....	28	No. 30 " "	24.....	140½	No. 32 " "
4.....	37½	No. 30 " "			

AN IMPROVED OIL CAN.


The accompanying illustration represents what is



THE RAU PATENT OIL CAN.

styled the "Perfection" oil can, of the Rau Patent Oil Can Company, Nos. 42 and 44 Michigan Street, Chicago, Ill. It is designed to save the time of the engineer and the mechanic using it, and to absolutely prevent any waste of oil. The construction of the can will be readily understood from the view given, the interior being shown within the broken-away lines, while the thumb piece by which the valve is operated is shown in the small view. The practical operation of the can is based upon the well known fact that, owing to the normal air pressure, the flow of any liquid from a closed vessel is almost entirely dependent upon the simultaneous admission to the vessel of a volume of air equal to that of the liquid discharged. Without such coincident admission of air, it would require a pressure of from fourteen to fifteen pounds per inch to force the liquid out of a closed vessel. In this can the admission of air to the interior of the can is effected by air holes in the push stem, by which the lever is operated to open a valve covering the inner end of the spout. The valve is mounted upon the end of a lever pivoted upon a center rest, the valves being made of polished brass, white metal, or leather, as preferred, or brass faced with leather, and are absolutely air tight, so that the instant the thumb pressure is removed from the button on the push stem, not a drop of oil can escape. The valve is firmly held to its place by lateral springs, made of a single piece of fine piano wire, coiled around the outer ends of the center rest for valve lever, the valve, the center rest, and the valve lever being all carefully grooved and fitted, so that the operation will be perfect and there will be no side motion lost. The end of the lever connecting with the valve is so made that no pressure is put on the rivet, the lever itself resting on the valve, and not on the rivet, when the can is closed, and should the valve become detached, it could not rest on the valve seat. The spring upon the push stem is of brass spring wire, so gauged and tempered as to retain its elasticity in any position, and it has a play of five-eighths of an inch, thus giving a similar play to the valve to allow of a full flow of oil when the stem is pressed down. With this can, no matter in what position it is held, the oil does not flow until the push stem is pressed down, affording great advantage in oiling

parts of machinery difficult of access, where the engineer or machinist frequently has to waste oil, when using the ordinary cans, in order to reach the parts desired. Also on the removal of the pressure from the push stem the flow of oil instantly ceases, the amount



CARSON'S ARC LAMP.


[FOR DESCRIPTION SEE PAGE 164.]

of oil remaining in the tube being held there ready to drop immediately when the tube is again pressed, thereby effecting a great saving of time. The oval shape in which the can is made is said to give general satisfaction, and they are regularly manufactured of the best charcoal tin, although special sets are made to order of brass or other metals.

IMPROVED LOCK AND SHACKLE FOR RAILWAY SWITCHES.

The device illustrated herewith is designed to prevent the possibility of switches to sidings being left open by switchmen and train hands, providing for holding the operator at the switch until it is moved to a position to open the main line. This invention has been patented by Dr. William H. Caine, of Stillwater, Minn. The switching rails are connected by a tiebar that leads to a crank on the target rod, the latter being supported by a switchstand having an operating lever formed with a folding handle adapted to enter recesses in the table of the stand. Beneath the stand is a box or case, preferably of sheet metal, into which the lower end of the target rod extends, where it is connected to a disk having a notch or recess in its peripheral face. In connection with the disk is arranged a vertical locking bar, with a key adapted to enter the recess in the

disk, the lower end of the bar being pivotally connected to a lever. This lever is fulcrumed horizontally in the case, its other end being connected to a vertical plunger, on one end of which is a spring abutting against the bottom of the case, the upper end of the plunger extending through the top of the case and carrying a step or platform. At each side of the plunger are pivoted shackles, with inwardly extending arms, and jaws which close as the plunger is depressed, and open as it rises. To open the way to the siding, the switchman places his foot on the step, when the depression of the plunger causes the shackles to grasp his ankle, and the simultaneous lifting of the locking bar at the other end of the horizontal lever lifts the key out of engagement with the disk connected with the



(CAINE'S SAFETY LOCK AND SHACKLE FOR SWITCHES.

lower end of the target rod, when the switch rails may be turned, and may be locked in such position by turning the handle of the operating lever downward to enter a recess in the table of the stand. The shackles

*From "Experimental Science," by Geo. M. Hopkins. In press. Munn & Co. publishers, New York.

will thus be locked upon the ankle of the switchman until the switch rails are again moved back to a position to open the main line, when the key of the vertical locking bar again enters the recess in the disk connected with the target rod, the spring forcing the plunger rod up, and the shackles opening to release the switchman.

NEW ARC LAMP.

The most prominent feature of all modern lamps is their vertical height, and yet where a lamp is required to burn all night this height is insufficient to permit of using carbons long enough for all-night illumination. In such lamps two pairs of carbons are used, one pair being burned until exhausted, when the other pair is automatically switched into the circuit, thus necessitating the adjustment of two carbons, and involving a serious waste in the way of carbon stubs.

The accompanying engraving shows a lamp recently invented by Mr. R. D. Carson, of Philadelphia, Pa. In this lamp a great length of carbon is contained in a small space, thereby permitting of the construction of a compact and symmetrical lamp which will burn throughout the night without the necessity of employing two pairs of carbon rods and shifting mechanism for transferring the regulator from one pair of carbons to the other.

Owing to its compact form this lamp is well adapted for indoor lighting. It has the advantage over the ordinary arc lamp in forming the arc in a horizontal plane, with nothing below the luminous point to obstruct the light. Its small size permits of making it very ornamental, and the length of its carbons renders it unnecessary to renew them oftener than once in two or three evenings, unless the lamp is used for all-night illumination. The vertical height of the lamp permits of using it in places where lamps employing ordinary straight carbons would be inadmissible.

The lamp is arranged to hold two curved carbon rods at an angle in relation to each other. Fig. 1 shows the complete lamp in operation, and Fig. 2 is an enlarged detail view of the interior of the lamp and the carbons, showing the arrangement of the regulating mechanism. The solenoid in this lamp is composed of two parts, the outer one being of coarse wire and arranged in the main circuit, the inner part being made of fine wire and connected in a shunt around the arc in the usual way. The two coils of the solenoid are connected so as to produce opposing effects upon a soft iron core.

The core carries a plate which supports a friction disk by means of springs, and a prolongation of the core carries a pinion which engages the bevel wheels on the carbon-supporting shafts. When the current is normal, the friction disk is carried upward by the movement of the core as it is drawn into the solenoid, thereby bringing the friction disk into contact with a frictional surface upon the lower end of the solenoid. This holds the carbons in a fixed position until the arc lengthens, when a greater proportion of the current goes through the fine wire of the solenoid, thus neutralizing the effect of the coarse wire coil, releasing the friction disk, and allowing the carbons to approach each other by their own gravity.

As soon as the resistance of the arc is reduced, the amount of current passing through the fine wire is diminished, when the current in the coarse wire of the solenoid draws the core up and checks the movement of the carbon rods by frictional contact of the disk against the frictional surface of the solenoid. When the carbons are in contact, the arc is formed by the upward movement of the core of the solenoid after the friction disk is in firm contact with the lower end of the solenoid.

The core is provided with spiral ribs which are capable of sliding through slots in the friction disk, so that after the latter comes to rest, the further upward movement of the core causes it to turn sufficiently to separate the carbons and form the arc.

Further information regarding this compact and simple lamp may be obtained by addressing Mr. R. D. Carson, Zoological Garden, Philadelphia, Pa.


Cotton Manufacture in Brazil.

The manufacture of heavy brown cotton goods in Brazil is developing gradually and successfully, says *Industries*. Even now both Great Britain and the United States of North America are considerably injured in their sales of such goods. It is feared, when the manufacturers in Brazil have attained a little more skill and perfection in this industry, that their goods will drive all others out of the native market. And this observation applies almost equally to all other kinds of cotton products. The raw material in use in the empire is brought from Pernambuco, and costs

about eleven cents per pound at the mills at Rio Grande do Sul. The retail price of one meter of brown sheeting, smoothly and evenly woven, of a weight per meter of 240 grammes, and of a width of 33 inches, is 16 cents. The price of the heavy cottons is about the same figure, but their breadth is less than that of the sheeting. The mills at Rio Grande do Sul are very prosperous. Last year they made improvements on extensive scale, and yet were able to pay the shareholders a dividend of sixteen per cent. At present the United States are very successful in supplying bleached and brown muslins and double width bleached cotton sheetings. The price of the last mentioned class of goods is about seventy cents per yard, and this limits their sales, being considered too high.

LAUNCH OF THE PHILADELPHIA.

This, the fourth of the new steel war vessels built by the Messrs. Cramp for the U. S. government, was launched from their shipyard at Philadelphia on Saturday, September 7. She was authorized to be built by the act of March 3, 1887, and the limit of cost fixed at \$1,500,000, but the contract was let to the Messrs. Cramp, with special modifications from the original specifications, for \$1,350,000. The law provides that she must exhibit a maximum speed of at least nineteen knots per hour. For every quarter knot in excess the contractor is to receive a premium of \$50,000, and for every quarter knot of deficiency he is to suffer a deduction of \$50,000. The Navy Department has prescribed a run of four hours at mean low draught for the speed test. According to the contract, the Philadelphia should be completed on October 27 next. This cannot be accomplished, but she is well advanced for a ship just



THE NEW U. S. CRUISER PHILADELPHIA.

off the ways, and the engine shafting has been put in place. The San Francisco, a sister ship now being built at the Union Iron Works, San Francisco, which should be completed one day earlier, will probably be launched about a month hence.

In the *SCIENTIFIC AMERICAN* of August 10 will be found an illustrated description of the Philadelphia, showing the several stages of her construction.

The Photographic Convention in London.

The photographic convention of the United Kingdom meets in London this year. An exhibition of photographic apparatus and photographs is now being held at the St. James' Hall in Piccadilly; excursions are being made daily to places of interest in or near London.

The photographic exhibition appeals as well to the general public as to the professional or amateur photographer. Upstairs in the balcony is a very fine and representative collection of "pictures"—photographic portraits of more or less pretty women, pictures of babies, interesting landscapes, historical buildings, etc., etc. Below, on the floor of the hall, are exhibited cameras, lenses, and plates, negatives of historical interest, enlarged pictures, chemicals, and the rest. As to the former, we may mention that it includes photographs by such well known artists as Friese Greene and Byrne & Co., of Richmond, as well as some interesting "platinotypes" by Keene, of Derby; among the latter is found apparatus from every well known optician and photographic chemist in London.

Being anxious to discover the objects and aims of the convention, a representative of *The Pall Mall Gazette* waited upon the president, Mr. Andrew Pringle, who was good enough to afford him a brief interview.

"This is the jubilee of photography, is it not?" asked the representative.

"Yes," replied the president. "It was just fifty years ago that the first account of Daguerre's process was published in France. Daguerre, as you may be aware, used by way of sensitized plate a plate of

silver which had been exposed to the vapor of iodine. The coating of iodide of silver thus formed was acted upon by the light in much the same way as the dry plate or stripping film of the present day."

"That was the beginning of all things, then, was it?"

"By no means. Previous to that—in January of the same year—Fox Talbot's process was given to the Royal Institution and to the world by Faraday. In the same month, Talbot read a paper on 'photogenic drawing'—so he called his new process—before the Royal Society. Talbot employed the chloride of silver, which he made by dipping the medium used, first in a solution of sodium chloride, or common salt, and then in a solution of silver nitrate. We do not claim that no photograph was produced before 1839; on the contrary, we know that Wedgewood and Sir Humphry Davy produced some long before. But they could not fix the fleeting image; a few hours of bright sunlight caused it to vanish without recall. In 1819, Herschel successfully employed the sodium hyposulphite for fixing; Talbot used it in 1839, and finally tried to patent it in 1841, but failed."

"So this is why you speak of 1839 as the jubilee year of photography?"

"There is yet another reason. In 1839 Mungo Ponton discovered the action of certain chromates upon gelatine. That gave rise to numerous processes, and is also the basis of an immense number of the photo-mechanical printing processes now in vogue. The first undoubted record of the use of a gelatine emulsion is that of Harrison, in 1868. He did not persevere in his labors, however, but left them to be taken up by Dr. Maddox in 1873. Maddox perfected the gelatine bromide process, which, with certain alterations and improvements, has been in use ever since."

"One may take it, I suppose, that great advances have been made since the tentative efforts of Daguerre and Fox Talbot fifty years ago?"

"Yes; but the advances have been made not so much in the direction of results—though these, of course, are remarkable—as toward the convenience and rapidity with which these results are obtained."

"What about the future?"

"Well, our great aim at present is to devise some method by which photography may be able to render in monotone the visual brightness of certain colors of the solar spectrum. For example, the deeper blues—indigo, violet, etc.—are largely used by painters to represent the darker shades of a picture. These colors, however, constitute the actinic rays of the solar spectrum; they have a more powerful action than any other upon the ordinary sensitized plate; consequently, they come out in the photograph

pretty much as if they had been white. We want photography to be orthochromatic, or color correct; and I may tell you that our aim is so far within our reach that plates have been prepared which prove to be more sensitive to the yellow rays than the blue."

American Association for the Advancement of Science.

At the session of this association recently closed at Toronto, Canada, the following officers for the ensuing year were unanimously elected: President—George L. Goodall, Cambridge, Mass.; Vice-Presidents—S. C. Chandler, Cambridge, Mass., mathematics and astronomy; Cleveland Abbe, of Washington, physics; R. B. Warder, Washington, chemistry; James E. Denton, Hoboken, N. J., mathematical science and engineering; John S. Brauner, Little Rock, Ark., geology and geography; C. S. Minot, Boston, biology; Frank Baker, Washington, anthropology; J. R. Dodge, Washington, economic science and statistics; Permanent Secretary—F. W. Putnam, Cambridge, Mass.; General Secretary—H. C. Bolton, New York; Secretary of Council—James Landon, Toronto; Treasurer—William Tilly, Mauch Chunk, Pa.

The association will meet next year at Indianapolis, on the third Wednesday in August.

THE PITTSBURG Commercial Gazette says: Few persons are aware that an aluminum-making plant is now in full operation in this city. This industry was established here during the winter by the Pittsburgh Testing Laboratory Company, and has proved a decided success. The product is obtained by a process of which electricity is a great factor.

About fifty pounds of aluminum metal are produced daily. It is worth about \$4 per pound, and this is a very large single output when compared with the product of the factories in other parts of the world. The material is used for various purposes. It has taken the place of silver leaf in sign painting, and in that particular has proved a great success.

THE HARLEM RIVER AQUEDUCT TUNNEL AND ITS APPROACHES.

When the subject of crossing the Harlem River by the proposed new aqueduct was considered, various means were discussed, one of them that of a viaduct, similar to High Bridge, and while it was believed that of the two methods the viaduct was thought to be the most costly, it was not so much on the score of economy as on that of safety that the method of a siphon tunnel was preferred.

Our first cut shows a longitudinal section of the tunnel and the shafts which were the base of operations during the long months of construction. The sections shown seem to be two in number, the upper one in coming to a stop at crevice in the river bottom, and the lower one running entirely across. Before the upper section was started, soundings were taken in the river bottom, and the indications of a firm bottom seemed conclusive. After the tunnel had been driven quite a distance, the roof appeared wet and heavy, and water seams became more and more troublesome. Prior to this the drill had been run down, with courses crossing from both sides of the river, so as to determine, if possible, the feasibility of going ahead. The indications from the drill were more encouraging than the work directly in hand; but it was thought best to persevere, as the enormous expense of sinking the shafts deeper was fully realized. So the upper tunnel was pushed ahead from the south side until the water came in such quantities, not from a crevice, as our artist has with some license suggested, but from innumerable small openings in all directions, that finally became too great to be successfully resisted. A strong bulkhead was then built in the upper tunnel, and the shaft known as No. 25 was sunk to a depth of 307 feet below mean high water. At the point indicated in the cut it had reached a depth of 157 feet. It was, therefore, finally put down 150 feet deeper. The distance from center of shaft 24 to that of 25 is 1,312 feet, and the internal diameter of the tunnel, which was circular in section, was 10 feet 6 inches, with an area of 86.59 square feet. This shaft is the deepest one on the new aqueduct, and altogether its depth amounts to 419.70 feet. The pressure of the water on this part of the tunnel is enormous, and the circular form is chosen because of its greater resistance. We have been informed that a steel shell made of riveted segments will be built as a lining to the brickwork, to add material resistance to this pressure. For some time experiments have been making, looking to the discovery of a substance with which all the circular sections of the new aqueduct may be lined, so as to diminish the great loss of water due to the perviousness of brickwork. It has been found, after repeated tests of many alleged superior washes, paints, gums, etc., that a thin coating of neat Portland cement of good grade, so thin as to be put on with a brush, is the most effective. We understand that these experiments are still going forward, and that no final report with recommendations has yet been made.

When shaft 25 is completed, it will be of a twofold character. It will be divided by a brick wall into two separated shaft chambers, one the aqueduct shaft and the other the pump shaft. In the latter will be constructed two inverted arches, the first one about 47 feet below the roadway, and the second one 16 feet lower.

Our second cut shows the operation of building a pair of inverted arches. The object of the lowest one is to resist any sudden upward pressure of water that may arise, and the upper is to re-enforce the lower one.

Passing from shaft 25 to 24, a point of striking interest is shown in our sketch, figured 3 and 4. Looking at Fig. 1 again, on the right hand, a jog or offset is shown in the vertical continuance of the shaft. Horizontally, it becomes a turn in the course, and it was done, we believe, in the hope of getting better ground to work in. This hope proved delusive, and it is now believed that it would have been better to have gone further north and sunk the shaft directly down, as an offset in a shaft of this character interferes with pumping or lifting. In the opening to the left the entrance to the lower shaft is seen. This jog in the course of the shaft is due, not to the reason assigned above, but to bad engineering. The alignment of the siphon tunnel deviated so much from its proper direct course as to make the turn horizontally necessary, as the siphon leg was progressed from the south northward entirely beneath the river to what was supposed to be its intersection in a vertical plane. Having ascertained the true position of the tunnel below, shaft 24 was turned and then driven down to meet it. This turn in the shaft necessitated two lifts to remove the excavated material, and also imposed the burden of emptying the siphon upon shaft 25.

In the fifth sketch is a view of the pump and aqueduct shafts, with four-foot blow-off pipe connections with a gate house. The blow-off pipes, which primarily are the outlets when the tunnel is to be emptied, also add to the safety of the shaft by providing means of relieving it of an excess of pressure should such ever occur.

The pump shaft is provided for the purpose of emptying the section of the tunnel between shafts 24 and 25 whenever a necessity for so doing may occur.

To this end great cylindrical iron buckets have been constructed, capable of lifting 1,350 gallons at once. They are shown in our sketch. The advantage of these huge buckets over pumps is as follows: The siphon will be emptied and cleansed out not oftener probably than once in nine months or a year, and this operation will occupy but a small interval of time. They are operated either by windlass or by a pony engine winding a cable about a drum. Attached to the cable, they are ready for instant action. Pump action is found serviceable only where there is some degree of constancy; irregular work promotes rusting of parts and damage to the operating machinery. The buckets are of the simplest construction, being made of boiler iron sheets of a cylindrical form and bolted together at the joints.

The reason assigned for sinking the shafts to such a great depth was that the bad character of the material made it necessary. This would be a sufficient answer if it were not true that much more difficult ground had been successfully tunneled by means of the freezing process. Why this process was not tried has not been successfully explained, the plan followed having added greatly to the expense of the whole undertaking and constituting one more addition to the sum of bad engineering.

The special provisions pertaining to the execution of the work are of the most approved character. All brick masonry shall be laid to a line, with the beds in the line of the radii of the curves and with joints not exceeding $\frac{1}{4}$ inch for either face or arch work. The inside faces of the joints shall have all the joints cleaned off, pointed, and left in a neat condition. The mortar and cement requirements are fully up to the standards established in this great work. In regard to the tunnel lining, the provisions of the contract call for cast iron rings $2\frac{1}{2}$ feet long, measured along the axis of the tunnel. The rings will be composed of ten pieces, put together by bolted flanges. The joints will be made with strips of lead, three inches wide and one-quarter of an inch more or less in thickness. The open horizontal joints on the interior face are to be filled with rust joints. All pieces to form rings are to be so formed as to be interchangeable. The joints between rings will be hub and spigot joints.

Shaft 25 was begun March 21, 1886, and sunk to a depth of 385 feet below river level, or the point at which the siphon tunnel started northward, July 1, 1887, or one year and four months. The siphon tunnel began August 1, 1887, and progressed as far as the vertical alignment of shaft 24, a distance of 1,312 feet, February 9, 1889, or about one year and six months. These figures do not give any basis for calculation as to the rapidity of excavation. Shaft 25 was begun March 1, 1886, and 261 feet had been excavated up to October 30, 1886. Time occupied 7 months and 29 days. Subsequent progress was delayed for reasons other than that of necessity, and are not to be considered in such an estimate.

The work under the Harlem and its approaches is no doubt the most difficult work undertaken on the new aqueduct, and from an engineering point of view perhaps the most unsatisfactory, either in its installation or economical execution.

Classification of Patents of Thomas A. Edison.

TELEGRAPHY.—Printing and automatic, 52; chemical and perforating, 34; perforating machines, 6; chemical stock printer, 1; multiplex, 17; relays, 8; switches, 2; phonoplex, 3; induction relay tel., 2; acoustic, 2; amr. and ind. signal app., 4.

ELECTRIC LIGHTS.—Incandescent lamps and manfr., 104; arc lamps, 4.

DISTRIBUTION.—Systems of regulation and indicating devices, meters, sockets, switches, 66.

GENERATION.—Dynamoes, motors, 3; transmission of power, 54; regulation, 50.

RAILWAYS.—Electric motor and tracks, 8.

CONDUCTORS, UNDERGROUND AND OVERHEAD, 3.

TELEPHONES.—Transmitters and receivers, 32.

BATTERIES, GALVANIC AND SECONDARY, 3.

PHONOGRAPH, 21.

ORE MILLING, 4.

MISCELLANEOUS.—Electric pen and stencil app., 66; typewriter, 3; shafting, 1; malleable iron, 1; vocal engine, 1; preserving fruit, 1. Total, 493.

Besides these he has over 300 applications for patents pending on all subjects.

The various interests bearing his name own many hundred other patents covering details and modifications of Mr. Edison's inventions.—*W. J. Hammer, Electric World.*

INCOMBUSTIBLE TEXTILES.—There are many substances which have the property of rendering the fabrics to which they are applied incombustible, but they usually spoil them, either by changing the color or stiffening them to such a degree that they cannot be used. An easy and safe way of protecting curtains and mosquito nets against fire is said to be by steeping them in a solution of phosphate of ammonia, obtained by mixing $\frac{1}{2}$ a liter of water (1 pint) with 100 grammes (about 3 ounces) of phosphate. In this way the color and texture remain unaltered.

Correspondence.

Astigmatic Eyepiece for Optical Instruments—A Correction.

To the Editor of the Scientific American:

Your issue of August 31 contained a reference to myself which is so preposterous that to the initiated it contains its own refutation. Nevertheless, to prevent possible misconception on the part of those who do not know me, I beg to be permitted to express my exceeding regret and annoyance at my name being used in your columns, as it certainly was, without my permission or knowledge. J. A. LIPPINCOTT.

To the Editor of the Scientific American:

The article in the SCIENTIFIC AMERICAN of August 31, 1889, on "Astigmatic Eyepieces for Optical Instruments," should have read 28,000 prescriptions from Dr. Lippincott and others. J. KORNBLUM.

Pittsburg, September 1, 1889.

Sugar as a Remedy for Boiler Incrustations.

To the Editor of the Scientific American:

It is now nearly three years since you brought to notice the experiment of an Italian engineer, employing sugar to prevent boiler incrustations. I tried it immediately afterward, with the success claimed, and have employed it ever since. Our feed water coming from a well, being excessively bad, we had great trouble to get rid of the scales. The boiler was very old, about thirty years, and we intended to buy a new one. So I thought, if any harm should come out of the sugar, there would be not much lost. With the sugar, of which I employed three pounds of the brown kind, and a handful of wash soda, in four weeks, we found a heap of sandy mud on the second sheet or above the grate, the flues being covered with scales as usual, but the scales were soft and easily removed. The same thing happened with new tubular steel boiler. We find most of the solid matter above the grate, and the tubes and boiler sheets covered with a thin adhering film of scales as high as the water reaches. Above the communication with the mud drum the tubes are thickly covered with soft scales after heavy rains, but under the scales the metal is as sound as when new. * * * A. BONENBLUST.

Tell City, Ind., August 13, 1889.

PHOTOGRAPHIC NOTES.

The Pyrocatechine Developer.—Dr. Carl Irna gives the following formula:

Solution A.

Sulphite of soda..... 100 grammes.
Hot distilled water.... 400 c. c.

Solution B.

Carbonate of soda..... 100 grammes.
Water .. 400 c. c.

Take 30 c. c. of A, 60 of B, and add one gramme of pyrocatechine.—*Revue Photographique.*

Prevention of Blisters in Albumen Prints.—Dr. Vogel recommends the use of a bath of alcohol, after toning and before fixing, as a remedy in obstinate cases of blistering. He advises alcohol at 70°. With our ordinary methylated spirit we should get at something near enough to this strength, by adding one part of water to four parts of the spirit at the strength at which, on the average, it is sold. An immersion of the prints for three minutes in this liquid before fixing will generally suffice to prevent blistering in cases when other means fail. Of course, if the spirit is used for more than one batch of prints, the water taken in with the photographs must be taken into account when reckoning the strength of the solution; and when any large number of pictures are to be immersed in a limited quantity of the diluted alcohol, it will be desirable for the prints to have the excess of water removed by lightly pressing a pile of them first. The alcohol itself then may be somewhat stronger to begin with.—*Photo. Review.*

Ink for Writing on Photographs.—The following answers very well for numbering and marking proofs, the writing being executed on a dark portion:

Iodide of potassium..... 10 parts.
Water..... 30 "
Iodine..... 1 "
Gum..... 1 "

The lines soon bleach under the strokes by the conversion of the silver into iodide.

Natural Gas for Balloons.

Prof. Carl Myers, who lately made a balloon ascension from Sandy Creek, N. Y., had the balloon inflated with natural gas from the gas well there. Nearly 1,000 people witnessed the ascension. Prof. Myers had been invited to Sandy Creek by the directors of the gas well for the purpose of testing the supply of the well. The experiment proved eminently satisfactory. The capacity of the balloon was 11,500 ft., and it took just thirty minutes to fill it, which would show an average flow of over 500,000 ft. per day. According to the present showing the well is a very valuable one, and the prospects are very flattering for a much larger flow as the drilling continues.

WITH MR. EDISON ON THE EIFFEL TOWER.

R. H. Sherard, representing the *Pall Mall Budget* (London), relates as follows his interview with Mr. Edison in Paris:

This is what Edison wrote to me, says Mr. Sherard, when I proposed he should grant me five minutes talk with him:

"All right. Friday about eleven in morning. I'll be sane by that time. My intellect is now making 275 revolutions a minute."

I called at the Hotel du Rhin at eleven o'clock, and was shown up to the handsome drawing room on the first floor. Edison was standing by the mantelpiece. At a secretaire by the window were Colonel Gouraud, Mr. Durer, and others; at the far end the sweet girl wife Mrs. Edison, surrounded by various persons. It is always difficult to begin, for one who has come to annoy, but I plunged into matters at once.

THE ORE-EXTRACTING AND THE FAR-SEEING MACHINES.

"About this ore-extracting machine," Edison said, "it's going to be a great thing. Already we have eighty machines at work in the iron mines. Yes, it is adapted for iron ore only as yet. I am studying the question of a machine for treating both refractory silver ore and gold ore, and shall get them out by and by. Then we shall make more money."

"The far-seeing machine?"—"I have heard," he said, "that some European inventors claim to have preceded me in this, but I do not know anything about their inventions. My machine is getting on very nicely. I do not think it will ever be useful for very long distances, and it is absurd to say that it will enable one to see another ten thousand miles away. In a city, however, it will be of practical use. I don't look for anything further, at least at present."

THE PHONOGRAPH AND THE PRESS.

"The phonograph?"—"We have got it into practical form. Already 1,800 machines are in use in commercial houses, and our factories are now turning out forty machines per diem. I have also, at last, been able to make a perfectly solid mailable cylinder, which can go through the post for any distance without risk of damage. All this has been very hard work. On the tools for making the big phonograph alone we spent \$5,000. I have also created a small model—a pocket phonograph, if you like to call it so—the cylinder of which will take 300 words, the length of an ordinary letter, and which will be very practicable for ordinary correspondence. I have the model here, and you can see it any day you like. These are not, however, yet ready for sale."

"What use can newspaper people make of it?"—"Oh, plenty. It is already used in the *World* office. The machine is placed downstairs. The reporters come in and talk into it. The cylinder is taken upstairs to the composing room, and the compositors set up from its dictation. They attain much greater speed, make more ems in an hour than on the old system, and earn more money."

IMPRESSIONS OF PARIS—"WHEN DO THEY WORK?"

"How are you impressed with Paris?"—"Oh, I am dazed. My head's all in a muddle, and I reckon it will take me at least a year to recover my senses. I wish now that I had come over in my laboratory blouse, and could have gone about unknown and have seen something. The exhibition is immense, larger than our Philadelphia exhibition. So far, however, I have seen but very little of it. This morning, however, I saw a tool which will save me \$6,000, clear, a year. It is a chisel worked by hydraulic pressure. I just saw it, passing by—just a glance. I shall order some, and send them out. They will enable us to reduce our labor by eighteen hands." "That's a good morning's business," said Colonel Gouraud. "Yes," said Edison, and continued: "What has struck me so far chiefly is the absolute laziness of everybody over here. When do these people work? What do they work at? I have not seen a cartload of goods since I came to Paris. People here seem to have established an elaborate system of loafing. Some of these engineers who come to see me, fashionably dressed, walking stick in hand—when do they work? I don't understand it at all."

EDISON'S RELIGION OF WORK.

"Over here we hear wonderful stories of your working. You have the reputation of being able to work twenty-three hours a day for an indefinite period."—"Oh! I have often done more than that, haven't I, Gouraud? As a rule, though, I get through twenty hours a day. I find four hours sleep quite sufficient for all purposes."

Edison pronounces the words "work" and "working" as some do "prayer," "religion." It is also a religion, it is true.

"I see you smoke. It does not harm you?"—"Not at all. I smoke about twenty cigars a day, and the more I work, the more I smoke." Some one remarked, "Mr. Edison has an iron constitution, and does just everything contrary to the rules of health. Yet he is never ill."

UP THE EIFFEL TOWER WITH EDISON.

I asked: "Beyond the far-seeing machine and the rest, are there projects?"—"Any number," said Edison. "When we make our big exhibition in America, I shall have to have several new things." It is perfectly useless to ask Edison for information as to ideas. In him everything is so practical that it seems he cannot talk about what is phantom merely. It is the "what is" with him, and not the "about to be."

Mrs. Edison then asked the Cavalier to do her the pleasure of lunching with her, *chez* Brebant, on the Eiffel tower. Colonel Gouraud asked me to be of the party, and together we went on to order breakfast. *En route* the Colonel asked me to contradict a story which has appeared that he brought to Edison a phonographic message from the Queen. "Mr. Edison received messages from the Queen of Italy, from the King, and from the Prince of Naples. I suppose that is what the story was based upon."

PREPARING TO OUTTOP THE TOWER.

"When on board the ship," said Edison, as we sat down to *dejeuner* on the terrace of the Eiffel tower, *premiere etage*, "they put rolls and coffee on the table for breakfast. I thought that that was a very poor breakfast for a man to do any work upon. But I suppose one gets used to it. I would like one American meal for a change—plenty of pie for a change." He then smashed the roll with his fist.

There were six of us—Mr. and Mrs. Edison, Colonel Gouraud, the Cavalier, and Mr. Durer, the author of a very remarkable brochure on Edison. And we had the world at our feet.

There were shrimps among the *hors d'œuvre*. Edison had never seen any. "Do they grow larger?" he asked, and added, "They give a great deal of trouble for small results."

"This Eiffel tower?" I said.—"The work of a bridge builder," said one. "No," said Edison decisively. "No. It is a great idea. The glory of Eiffel is in the magnitude of the conception and the nerve in the execution. That admitted, and the money found, the rest is, if you like, mere bridge building. I like the French," he added. "They have big conceptions. The English ought to take a leaf out of their books. What Englishman would have had this idea? What Englishman could have conceived the statue of Liberty?"

"Will you beat the tower in New York?"—"We'll build one of 2,000 feet. We'll go Eiffel 100 per cent better, without discount."

IS A THOUGHT-RECORDING MACHINE POSSIBLE?

"Could not," I asked, "a machine be made which could be adapted to the head, and which would record one's thoughts, saving the trouble of speaking or writing?" Edison reflected. "Such a machine is possible," he said; "but just think if it were invented. Every man would flee his neighbor, fly for his life to any shelter."

As they brought in the *filets a la Brebant*, I said, and thought of little Dombey, "What is electricity after all?" He said, "It is a mode of motion, a system of vibrations. A certain speed of vibration produces heat; a lower speed, light; still lower, something else."

THE REIGN OF HUMBUG.

"Is there anything in electricity as applied to medicine?"—"There is a great deal of humbug in all that," he said. Then as a careful *maitre d'hotel* brought in the cradled *Clos Vougeot*, and served it with exaggeration of anxious ceremony, he added, "There is a great deal of humbug about wine too. And about cigars. Men go by cost. The connoisseurs are few. At home, for fun, I keep a lot of wretched cigars, made up on purpose in elegant wrappers, some with hairs in them, some with cotton wool. I give these to the critical smokers, tell them they cost 35 cents apiece. You should hear them praise them."

THE EDISON "SANATORIUM."

We talked of cooking and of famous *chefs*. Also of one who recently engaged a French cook at a bishop's salary. "Bright's disease of the kidneys is all the dividend that man will draw," said Edison. He seems to take delight in commercial phrases. It is comfortable to hear him pronounce the words "make money." Commerciality with him is dignified and impressive, vulgar as it is with others. The breakfast was *recherche* in the extreme, but Edison barely touched anything. "A pound of food a day is all I need when

I am working, and now I am not working." One could not help thinking of Chatterton and his crust.

After dessert there was champagne, and toasts were drunk. The Cavalier began. Edison said: "The Cavalier is profuse, but not so much so as another Italian gentleman who once proposed my health, and remarked that even the chickens in his country knew my name.—It's a regular sanatorium," he remarked later on, "so much 'health' being distributed." Again, "All this is new to me," alluding to the ceremonial of our festivities. "If I stay long here I shall too soon be able to get up and make speeches and wave my arms." When the coffee and cigars came in his face brightened up. "Mr. Edison is beginning to breakfast," said the Colonel. "Yes," said Edison, taking an Havana; "my breakfast begins with this."

THE MAN AND THE MONUMENT.

A few minutes later, happening to pass the tower, I saw at its foot again the man, with his face boyish almost for its openness, and the gray hairs over the unwrinkled forehead. Then I looked at the monument first and then at the man. The monument thus contrasted appeared infinitesimally small.

The Deadly Alternating Current.

The East River Electric Lighting Company, at its dynamo-house, East 24th St., this city, employs the Thomson-Houston system of electric lighting, using in all its outside lamps the direct current. But in the dynamo room is one machine which generates the alternating current, and this is used to supply the incandescent lights in the building, and, recently, for experiments by the Perry Motor Company. This one machine generates 1,000 volts power, and has not been long in the building.

On September 2, says the *N. Y. Times*, something went wrong with the switchboard connected with this machine, and Darwin A. Henry, the superintendent of construction of the company, undertook to set it right. He climbed up on the short ladder used to reach the switchboard, and started in on his work. He had been thus engaged for about five minutes when he attempted to turn part way around on the ladder. In some way one of his feet slipped, and for an instant he was in danger of losing his balance. Instinctively his arms were thrown up to recover himself. One hand came in contact with the negative terminal on the board, and hardly had he touched it when the other had struck the positive pole. The effect was instantaneous. The unfortunate man's hands remained as if glued to the death-dealing wire, his head dropped over on one shoulder, and in that position he remained for some moments. He did not utter a sound. There were two other men, named Thomason and Smith, working in the room, and one of them after a few seconds caught sight of his chief resting apparently with all his weight against the switchboard. Both men rushed to his assistance, but the man was dead. They tore his hands from the wires and lifted his body down and laid it on a bench. One of his hands—the right one—was terribly burned, the flesh having been consumed to the bone. The other hand was burned, but not so very badly.


Medical help was at once summoned. Dr. L. D. Henderson and Dr. W. C. Feeley were at the superintendent's side within ten minutes, and worked hard in trying to restore animation, but they might as well have tried to put life in a stone. They injected, hypodermically, quantities of brandy. Sylvester's system of artificial respiration was called into use, and they tried with a galvanic battery to bring the man back from death. But all efforts were absolutely useless, and after two hours of hard work the weary physicians were obliged to abandon their task and declare their patient dead.

There had not been a single evidence of life in Henry from the time he touched the wires. When the doctors reached him, the heart had ceased to beat and there was no sign of respiration.

In the opinion of both physicians, Henry's death was instantaneous, and, if the absence of any contortion either in body or face proved anything, it was a painless one. The burns in the hand, both the physicians and the employes in the building believe, were caused when the hands were torn away from the wires and after the man was dead. The separation created an arc, and without an arc there can be no burns.

Mr. Henry was about thirty years old, unmarried, and had been a practical electrical engineer from his boyhood. He was a capable electrician, and had much experience in handling electric apparatus, and was highly regarded by his employers.

The final argument on the question of the constitutionality of the new electric execution law, a question which involves the disputed power of an alternating current to kill, will be held at Buffalo within a fortnight, and this case may have considerable weight in the argument. It is proposed to use an alternating current of from 1,500 to 2,000 voltage in these executions, and it is contended that that force would not be sufficient to kill. In this case a 1,000 volt current, even when only accidentally applied, did its awful work effectually.



AN ATTRACTIVE CHEAP DWELLING HOUSE.

Illustrated herewith is a commodious dwelling house erected on Armory Hill, Springfield, Mass., and at a cost of \$3,600. Width, 31' 6"; depth, 44' 6", not including piazza. Height of first story, 9'; second story, 8' 6"; contains all the latest improvements and conveniences. There is a cellar under whole of house, containing a furnace and laundry; all furnished in the best manner. The exterior is covered with beveled white pine clapboarding, gables filled with shingles; slate roof. The hall is furnished with an ornamental staircase, with newels, posts, balusters, and rail, all handsomely turned of ash. The landing on staircase contains a pretty window glazed with stained glass. The door and window casings are neatly beaded, and turned sunk angle blocks are provided at angles. The trim is of ash. Open fireplaces provided with hearth and facings of rich tiles and handsome hard wood mantels. Five bedrooms on second floor, and bathroom. Large closets well fitted up with drawers and shelves. From front bedroom, door to veranda. The bathroom is fitted and finished in the best manner. The engraving was prepared from a photograph of the building taken specially for the ARCHITECTS AND BUILDERS EDITION of the SCIENTIFIC AMERICAN, and appeared in the August, 1889, number of that pub-

take better care of his money than the insurance company can, generally proves to be the man who is not able to take care of it at all. 6. Why some men, who say that their whole lives are devoted to laying up a competency for their families when they are gone, never seem to think of the simplest and quickest method of accomplishing that object—taking out a policy on their lives and paying a weekly premium. 7. Why it is generally necessary to carry the blessings of life insurance to a man's house and thrust them upon him, while he is frequently ready, unsolicited, to spend his money for things that are not blessings at all.

Mexican Mahogany.

The other day *The Timberman* visited Mr. Fred Schindler, who has recently returned from Mexico, and learned something about the fine mahogany logs which that gentleman secured for the firm of J. Rayner during his sojourn in the sunny southern climes. Mr. Schindler is a close observer, and his comments on the manners and customs of a race we know little about are interesting in the extreme. On his first visit to Mexico he was greatly surprised to find how little was known about it in the United States. The portion visited by him has been invaded by very few foreigners, and is about two hundred years behind the

Mr. Schindler has secured some very fine logs, which are now on their way to this market. Upon their arrival he promises to show some of the finest mahogany ever brought into this city.

The scarcity of mahogany at the old points of supply is leading to research into new fields. Some stock is now being cut in South America, but the quality is not up to the Mexican. It is probable, however, that as the hunt is carried further into the vast and hardly explored forests of this country, better results will follow.

Aluminum.

At a recent meeting of the Academy of Sciences, San Francisco, F. Gutzkow delivered an address upon the subject of the manufacture of aluminum. He claimed that no real progress had been made with this metal, and that the only chemical achievement of recent years was to reduce the heat which permits the use of cast iron. It is a comparatively unknown metal of great lightness, being one-fourth the weight of silver and one-third of that of iron. Its lightness makes it especially desirable in the construction of mathematical instruments.

It is very malleable, and is of a clay color. Sulphuric, nitric, and like acids have no effect upon it.



AN ATTRACTIVE CHEAP DWELLING HOUSE.

lication, together with the plan views of the first and second floors. The same number also contains engravings of several other attractive dwelling houses, costing from one thousand dollars to eight thousand dollars and upward.

Life Insurance.

Under the heading "Seven Things Hard to Explain," the *Insurance World* copies from *The Metropolitan* the following seven queries, which are calculated to set heads of families to thinking.

1. Why some men who are willing to toil and strive and save, that their families may be comfortable while they are alive, are not willing to pay a few dollars a year that their families may be kept from want after they are dead. 2. Why some men who are so prudent that they will not trust the welfare of their loved ones to the strongest life insurance company in the land, are, nevertheless, willing to trust it to the most uncertain of human chances—the contingency of their living long enough and being fortunate enough to earn and save a competency. 3. Why, on the other hand, some men who are so unsuspicious that they will trust an acquaintance who has not a dollar in the world to almost any extent, will, nevertheless, hesitate to trust a life insurance company that guarantees its promises with millions of assets. 4. Why some men who could not rest a moment if their houses and stores and factories were not insured, never think of the importance of insuring their lives, by whose productive power those houses and stores and factories were acquired. 5. Why the man who refuses to insure his life because he can

times. But northern capital and energy is gradually stretching out in that direction and finding an ample field. Strangers are still looked upon with distrust, and are not admitted to domestic relations with the natives. The agricultural possibilities are almost unbounded. Anything can be raised except the northern fruits, and so prolific is the soil that three crops of corn are frequently harvested a year. The climate is very unhealthy, and sickness prevails in all localities.

Mahogany in Mexico is becoming very scarce, and one is now obliged to go two or three hundred miles from the coast to secure first-class stock. The logs are cut during the summer months, hewn square, and then lie in the woods to await the fall freshets. These begin about the first of October, and the rivers, which have been dry for months, become rushing torrents. The logs are then thrown in and tumbled down the mountain sides until they reach more level country, where they are collected into rafts and continue their journey to the gulf. Here they are loaded into ships and thus reach the American market.

As to the size of the logs there is, to use Mr. Schindler's words, "practically no limit," some cut by him being 100 feet long, and will square four feet at the top. Of course, such logs as these are too unwieldy for transportation, and are therefore cut into fourteen or sixteen foot lengths. The export duty on logs is \$2 a ton, and this is charged on the tonnage of the ship. If there is any deck load, it must be paid for extra, at the same rate. And for every dollar of duty paid there must be affixed to the certificate a two cent revenue stamp.

but it makes no resistance to hydrochloric acid or to alkalies. In its alloys the best is made with copper, the color being gold. It is used largely in making watch cases and chains. As it does not corrode, it can be used in cooking, but its dirty appearance, together with its liability to become perforated by soaps, which eat it very rapidly, renders it quite undesirable. Its manufacture out of clay the speaker ridiculed as an impossibility, and he claimed further that there had never been an authenticated case of such manufacture. —*Pac. Lumberman.*

Continental Wages.

A stay-at-home man can have only a very vague idea of the position of England as compared with foreign countries. Especially he can have little idea how much leveling up has to be done with the wages of most Continental workers. If we say that from a half to one-third of our wages is the rate over vast regions of the Continent, we should not be far wrong. They are excessively low in some districts of southern Italy, as on the plains below Vesuvius, where five shillings a week for a man is not uncommon, and the agricultural laborer of Bohemia is not much better off. The normal condition, almost everywhere, is so far below ours that it constitutes a danger to us and a cause for the migration of trades, which are always seeking the easiest and most profitable lines.

A traveler who during the last three years has traveled over 30,000 miles of various European countries, declares that he has not once seen wages equal to those at Nottingham. —*Manchester Textile Mercury.*

The Meeting of the American Geological Society at Toronto, Wednesday and Thursday, August 28 and 29, 1889.

A movement for the formation of an association to include all the geologists of North America has been on foot some years, but actual organization was not effected until last December, and the first meeting at which papers have been read has just been held at Toronto, Ontario, in connection with the thirty-eighth annual meeting of the American Association for the Advancement of Science. The formation of the American Geological Society was first seriously suggested at the Cincinnati meeting of the A. A. A. S. in 1881, with the result that a committee, consisting of J. Proctor, of Kentucky, C. H. Hitchcock, of New Hampshire, H. S. Williams, of New York, N. H. Winchell, of Minnesota, and S. A. Miller, of Ohio, was appointed to get suggestions as to the new society. The circular which this committee issued received wide and cordial response. At Montreal the following year the committee reported results, and another committee, of which N. H. Winchell was chairman and C. H. Hitchcock secretary, was appointed to draught a constitution.

Several of the older and more conservative members of the A. A. A. S., however, at that time were opposed to the formation of a geological society, thinking that it would operate disastrously to the association at large, so that the only thing that was accomplished at Montreal, besides the drawing up of a provisional constitution which was not really adopted, was a resolution recommending the establishment of a geological journal. Soon afterward the *American Geologist* was established to supply the demand thus expressed.

For several years nothing further was done toward organization, though the matter was kept alive by correspondence; but after the *Geologist* had become fairly established, a renewed appeal was published in that journal by the Montreal committee that all persons interested in the formation of a geological society should meet at Cleveland, in 1888, in connection with section E of the A. A. A. S. This time the movement was destined to be a success, for most of the prominent geologists of the country who had formerly opposed such a society or had been indifferent to it were now urgent advocates of it. This decided change was brought about by complications which had arisen in connection with the International Geological Congress and the American committee thereof, partly on account of the cumbersome machinery of the great American Association for the Advancement of Science. From the Cleveland meeting of the A. A. A. S., therefore, dates the actual existence of the American Geological Society. The meeting at Ithaca last December was merely to complete the organization, and has received due notice in the columns of the SCIENTIFIC AMERICAN.

Last week, Wednesday morning, after the geological section of the A. A. A. S. had completed its organization for the Toronto meeting, it adjourned temporarily and Prof. Alexander Winchell, of the University of Michigan, called the Geological Society to order and gave a very encouraging report of progress. The 112 "original fellows" have received additions, until now the society has 175 members, and a good working surplus in the treasury, and includes within its ranks all the noted living geologists in the United States and Canada, with one exception. When Prof. C. A. White, vice-president of section E, had concluded his interesting and valuable paper on the Mesozoic rocks of North America in the afternoon, a provisional constitution was laid before the Geological Society. One of the main features of this was the provisions for membership. Members are of four classes: Original fellows, fellows geologists resident in North America, corresponding members geologists residing outside of North America, who have rendered special service to the science, and patrons, those who have done some great favor to the society. The matters of voting by proxy and publication aroused some discussion, but were referred back, together with the remainder of the constitution, to the committee to be laid before the society again at the annual meeting in the winter with whatever suggestions might be offered by fellows in the meantime.

Thursday was the day for papers, and section E had adjourned out of respect to the society; indeed, this step was almost necessary, for most of the members of the former belong also to the latter. Many of the most noted geologists on the continent had gathered together when the meeting of the society was called to order in the theater of the Normal School; among them were the world renowned Prof. James D. Dana; the equally celebrated paleontologist, Prof. James Hall, the president of the society; the great paleobotanist Sir J. W. Dawson; Dr. A. R. C. Selwyn, director of the Canadian survey; Prof. G. K. Gilbert, assistant director of the U. S. Geological Survey; Prof. T. C. Chamberlin, president of the University of Wisconsin. Between forty and fifty fellows were in attendance, all of them earnest workers in some department of their great science.

President Hall's opening address was an interesting statement of the origin and history of geological societies and associations in America. The first society for furthering geological science was formed in 1824 by a few enthusiastic students, but it was short-lived. In 1840 the scientists engaged in the State geological surveys throughout the United States united themselves into the American Geological Association, with the especial object of devising a suitable nomenclature for the formations of this country. After a few years this society was united with a society which had been formed by the naturalists, and the new body took the name of the American Association of Geologists and Naturalists. The physicists and chemists soon joined this society, and the present great Association for the Advancement of Science was the result. Out of this association again has sprung the new Geological Society.

After Professor Hall had concluded his address, Professor Dana gave an elaborate paper on "Areas of continental progress in North America, and the influence of those areas on the work carried on in them." In the first part of his communication the author described the three great Archæan and Paleozoic depressions or valleys of the Atlantic; the inland sea of central New York and eastern Ohio, which in later Paleozoic times was partly shut off by the island of the Cincinnati uplift from the remainder of the great continental ocean; and the great regions of the Rocky Mountains and the far West. On account of the great development of Silurian rocks near Lake Ontario and the perfection of their fossil remains, he suggested that the term Ontarian be substituted for Silurian in local phraseology. Especial interest attaches to this paper because in it Professor Dana practically reviews his own "Manual of Geology," bringing out his conclusions from recent observations all over the world, and showing wherein important statements and theories given in the manual must be modified. Professor Dana has attended none of the meetings of the A. A. A. S. for several years, and his presence at this meeting and active participation in the session of the Geological Society were a great encouragement to the new society.

The next two papers were by Professor Hall, and were entitled "Some suggestions regarding the subdivision and grouping of the species usually included under the generic term *Orthis*, in accordance with external and internal characters and microscopic shell structure," and "On new genera and species of the family *Dictyospongiæ*." Professor Hall contented himself with giving a mere sketch of an elaborate memoir which he has prepared on these subjects. The figures illustrating the morphology of different species now included under *Orthis*, and those showing the recent and great enlargement of the family *Dictyospongiæ* by the discovery of new genera and species, were examined with great interest by the fellows present. The *Dictyospongiæ* include forms that aroused much discussion when they were first discovered, which were called *hydnoceas* by Conrad, in the belief that they belonged to the cephalopods, but were named *dictyophyton* by Hall, because he thought them to be plants. Later discoveries proved the existence of siliceous spicules, and showed the true position of the strange organisms to be with the hexactinellid sponges. In discussing this paper Sir William Dawson pointed out that though these sponges are confined to the Devonian in New York, they have been found as far back as the Cambrian in Canada.

After the noon recess Professor Alexander Winchell occupied the chair in the absence of the president. The first paper on the programme was by Professor G. K. Gilbert, on "The strength of the earth's crust." The treatment of the subject was mathematical and theoretical. The author's observations were made largely in connection with tracing the history of the Quaternary lake Bonneville in Utah. From the phenomena of that locality and elsewhere, Professor Gilbert deduces the theory, which he holds only tentatively, that mountains are sustained by the strength of the earth's crust, while broader elevations, such as continents and continental plateaux, are sustained by virtue of the fact that such parts of the earth's crust are of lower specific gravity than those beneath the oceanic depressions. This communication naturally aroused some discussion among the fellows, the general tenor of which seemed to be that the strength of the crust was greater than Professor Gilbert's calculations made it.

In the absence of Professor Joseph Le Conte, his paper "On the origin of normal faults and of the structure of the basin region" was read by Professor J. J. Stevenson, the secretary of the society. Normal faults are those in which the downthrow of the strata is on the upper side of the plane of faulting or hade. Professor Le Conte would assign these faults to the oscillations of a somewhat mobile crust floating on a liquid interior. Without discussing this communication, the society passed to President T. C. Chamberlin's paper on "Boulder belts distinguished from boulder trains; their origin and significance." This

gentleman has made especial study of the glacial geology of this country for the U. S. G. S., and probably knows more about the drift than any one else in the land, so that his remarks were listened to with great interest. He said that for obvious reasons boulders were among the first phenomena of the drift to attract attention, but afterward study was diverted to other phenomena of this formation. Recently, however, much work has been done on boulders. Boulder trains had their origin in knobs or prominences of rock which gave off fragments as the ice passed over them. The boulders decrease in size with the distance from their source, and are arranged in somewhat divergent lines which might appropriately be called boulder fans. In a particular fan the boulders are usually of similar material. Boulder belts lie transverse to the direction of motion of the glacier, and are commonly associated with terminal moraines. Their striking characteristics are that the boulders are of many kinds of material and that they are superficial and do not mingle deeply with the drift, as do those of the trains or fans. A glacier deposits material in three ways: 1. It pushes matter forward mechanically, ridging it at its edge, forming what may be called push moraines. 2. A glacier may fail to carry forward to its actual extremity the material which it is pushing at its base, and this may lodge under the margin, forming a sub-marginal accumulation, which may be called a lodge moraine. 3. A glacier carries forward the material embraced within the ice or borne on its top until it reaches the extreme margin, when it is dropped, forming what may be called a dump moraine. The boulder belts are held to belong to the third class. Most of the boulders in Illinois, Indiana, and Ohio come from the Archæan rocks 300 to 500 miles northward, and are arranged in belts.

Professor C. D. Walcott's paper on a "Study of a line of displacement in the Grand Canon of the Colorado, Arizona," was read next. It was well illustrated by maps and diagrams, and showed how the dip of horizontal rocks might be made almost vertical near displacements or faults. Following this was an elaborate and valuable paper by Professor J. F. Kemp on "Trap dikes near Kennebunkport, Me.," which gave the results of much careful work in the field and with the microscope.

Papers by Messrs. J. S. Newberry, J. W. Spencer, D. Honeyman, and P. Neff were read only by title, and one by Mr. E. O. Hovey was referred to section E for reading. The Geological Society of America then adjourned to meet in the American Museum of Natural History, New York City, on the 26th of December next.

E. O. HOVEY, Ph.D.

Free Baths at Milwaukee.

Milwaukee is never behind in anything, not even when it comes to a public natatorium. The new free bathing establishment has been completed and turned over to the city.

The building, which is located on Prairie Street, near Seventh, is a handsome structure, and is very conveniently and neatly arranged, says the *Evening Wisconsin*. It is a solid brick building with stone trimmings. The visitor enters the building in the front, passing through a short hall between two rooms into the natatorium. A wide walk leads around the tank, which occupies nearly all the ground floor space. The tank is about 3 feet deep in front, the bottom sloping to the rear, where it is 9 feet deep. It is 32 feet 6 inches wide and 80 feet 6 inches long. Long lines of steam pipe run along the walls above the ground floor to heat the building, and above them are rows of ventilators. Two tiers of galleries run around three sides of the building, which are reached by eight flights of stairs. Each gallery on the sides is filled with a line of dressing closets, while the galleries at the rear end are fitted up with shower baths.

There are 108 of the dressing closets and 16 of the shower baths. The baths on the outside are counterparts of the dressing closets, but are different on the inside. They have zinc floors and the rose is elevated slightly above the top of them. Warm and cold water can be showered at the will of the bather.

Light is obtained through a long skylight running down the center of the roof. Closets of improved pattern have been arranged in a room to the left of the entrance. The room at the right of the entrance will be used for the office. On the second floor, at front of the building, is a suite of rooms for the janitor. A big boiler in the rear will furnish the steam to warm the building and the hot water to warm the water in the tank.

RELIEF OF DEAFNESS IN OLD AGE.—Sapolini, of Milan, has described a method of his which he states he has successfully employed in sixty-two cases of deafness of old age. It consists in mopping the membrana tympani with a weak oleaginous solution of phosphorus. He claims that the treatment diminishes the opacity of the membrane, increases the circulation, and improves the hearing.—*Kansas City Medical Index*.

[SPECIAL CORRESPONDENT OF THE SCIENTIFIC AMERICAN.]

THE PARIS EXHIBITION.

PARIS, August 25, 1889.

I hear from many quarters that there is great satisfaction at the sales of machine tools by the exhibitors. Some, indeed, have sold nearly the whole of their exhibits—an example in point being G. Lomont, who has sold a dozen machines out of the thirteen he exhibited. Wm. Sellers & Co., of Philadelphia, Pa., have sold their tool-grinding machine and their twist drill grinder to the Northern R.R. of France. Warner & Swasey, of Cleveland, Ohio, could have sold their exhibited machine two or three times over if they had a good attendant interpreter in charge, and it seems a great pity that so fine an exhibit should be left without anybody to show it.

There are very few machine tools shown at work in the exhibition, I am sorry to say, those of J. A. Fay & Co. and Wm. Sellers & Co. forming the praiseworthy exceptions. There are plenty of visiting mechanics here who have used twist drills, but never appreciated the advantages of a twist drill grinding machine until they saw one ground on the Sellers machine and put to work in this exhibit. The fact is that grinding a twist drill correctly by hand is one of those things that cannot be done, no matter what the experience or how skillful the mechanic. Sometimes one cutting edge only will cut. At others, each cutting edge will cut for a part only of its length, the amount of the clearance will be variable on the two cutting edges or at different points along the same cutting edge, and so on. But in the Sellers exhibit one sees that from the moment the drill point begins to cut, two distinct shavings of equal thickness and length are cut, and their strength is such that they will remain intact while emerging five or six inches from the mouth of the hole, and require quite some force to break them, whereas a badly ground drill will break up the shavings or chips, doing less work, and requiring more power to drive.

In an exhibit by P. Hure, of Paris, I find some milling cutters in which the front face, instead of being a radial line, has rake given to it, by making its plane on a line behind the center, after the manner of the teeth of a skew bevel gear wheel. For wrought iron, cast iron, or steel this is doubtless an advantage, but it is decidedly detrimental if the cutter is to be used for brass work. In this same exhibit I found a lathe in which, the slide rest being of the usual square top pattern, the tool is clamped to the underneath face of the square top, thus making the top surface of the tool steel the base from which the height of the tool steel with reference to the work is determined. The tool is held to the rest by two clamps, each having two screws. One of these screws (that nearest to the tool) passes through the top of the slide rest, and threads into the clamp, while the other threads through the top of the slide rest, while its point acts against the clamp. The first named is screwed up to lightly grip the tool, and the other is then screwed up, causing the clamp to act on the tool as a lever whose fulcrum is the front screw.

This is of course a very firm method of gripping a tool, being, in fact, that employed on what is known here as the Maudslay slide rest. It has not found favor, however, in the United States, and is not likely to do so, because it can only be applied to a compound slide rest, and small lathes are much better, if made on the American plan (as pointed out by me in a previous article), without any compound rest. While on this subject, let me say that the objectionable feature of the upper slide of a compound rest coming so close to the back head of the lathe that the upper feed screw of the rest cannot be worked without taking its handle off at every half revolution, is overcome in two exhibits here by the employment of a pair of gear wheels, one of which is on the end of the feed screw, and the other geared into it, the band being on the shaft of the lathe, and hence thrown out toward the workman. In one of these devices the gears are of equal diameters, while in the other, that on the feed screw is twice the diameter of that which the handle drives. The latter is, I consider, preferable, because it throws the handle well out from the tail stock of the lathe, while it enables the slide to be fed very finely to the cut.

In the exhibit of E. & P. H. Bonhey, there is a lathe in which what is usually the live center is a fixed dead center, a plan that certainly insures true work, whatever disadvantages in other respects it may possess.

On some of the small lathes for fine work the fit of the slides to the slide rest ways are made by gibs of brass or bronze, a plan adopted by Holtzaphel in his expensive lathes. My experience is, however, that cast iron is a better and more durable material, because the duty is not sufficiently heavy to cause the surfaces to cut, hence the cast iron gets a hard glaze that prevents wear. It must not be forgotten too that these gibs are right under the eye of the operator, hence their lubrication is not likely to be neglected or forgotten.

A point that seems to be overlooked in most slides and sliding heads is that there is, if the top face of the slideway is left a full plane surface, the sliding rest

is sure to get loose in the middle, because it is more used there than at the end of the slide, and it becomes obvious that instead of the surface in contact being greatest at the end of the slide, it ought to be the




Fig. 1.

least there, so as to equalize the wear. This is accomplished in one of the exhibits here by recessing down the slide faces at the ends, making the width of bearing at the ends rather less than it is in the middle of the slideway length.




Fig. 2.

My attention has been called to the samples of vise work exhibited by the French technical schools, and the following examples will give an idea of the whole and show their applications in practice. One of the simplest of these exercises is shown in Fig. 1, in which




Fig. 3.

the bedding of the surfaces *b* is an easy operation, but the fitting of the parallel faces *a* requires considerable skill. Figs. 2 and 3 are examples in the fitting of dies in connecting-rod straps, such as have already been referred to and illustrated in my previous letters. Fig. 4




Fig. 4.

is an example such as is met with in bedding the brasses of pillow blocks and locomotive axle boxes, and teaches that the patterns for such work should be so made or shaped that the surfaces *a* should, when the first bedding contact occurs, be quite clear of bedding,




Fig. 5.




Fig. 6.

or, in other words, that the surfaces *b* should not meet when surfaces *a* come into contact. The reason for this, the student soon discovers, is that it requires more metal to be cut off *a* and to let the top piece *c* down a given distance than it would be required to cut




Fig. 7.

off *b* to let *c* the same distance; and if, when bedding first occurs, it is at *b*, then but little will require to be taken off *b* to let *a* and *d* come into contact. This is a point often overlooked by pattern makers when mak-

ing the patterns, and by fitters or vise hands when fitting such pieces together. Fig. 5 is an example in which *a* is a bolt whose head *b* fits into a recess in *C*, and unless the sides *c*, *d*, bear with equal force of contact, the body of *a* will bind in *C*, and there will be a tendency to cause the head of *a* to bed unfair. Fig. 6 is a nut with a triangular hole passing through it, and from it the student learns how difficult it is to file up a true hexagon, and also to file out a triangular hole without cutting too deep into the corners. Triangular files with a safe edge are rarely kept, save in shops where very small work is done, and it is a frequent occurrence for the workmen to have to grind the teeth off one face of file in order to get a sharp corner to file out the triangular corners with. Fig. 7 is a strap key and gib for a connecting rod, and illustrates the point mentioned in one of my former letters that the French and Belgians sometimes use much less taper on their connecting-rod keys than is the practice in either America or England. As a natural result of this it takes more downward motion of the key to take up a given amount of wear, hence the employment of the piece or sleeve *a* in the figure, which takes up the length occupied by the long thread on the key end.

JOSHUA ROSE.

The Porpoise.

The French *Journal Officiel*, says *Nature*, recently contained a report which Prof. Edmond Perrier had sent in to the French government on the subject of the best means of protecting fishermen against porpoises. Although the depredations of these creatures have been exaggerated, it is certain that they do considerable damage, especially on the Mediterranean coasts of France, by tearing the nets. For at least a quarter of a century past efforts have been made to lessen the numbers of the porpoises by offering a reward per head and by other remedies. In 1865 the government invited the fishermen themselves to organize a seine net fishery for porpoises, and they were offered special nets, and sums of from 5 to 25 francs for each animal. It was, however, found in practice, that as soon as the porpoises felt themselves to be surrounded, they simply jumped over the seine nets and were at large again. Some years later the fishermen of Cannes, Saint Tropez, and La Ciotat petitioned government to lend them a gunboat, filled with torpedoes, for the purpose of firing at the porpoises. This was done, and the cannon and the torpedoes scared away the porpoises for about eight days, but they scared away the fish as well, so that there was no fishing for at least a week. The porpoises, moreover, are too numerous and too agile to be shot, one by one, in an effective manner. The report sums up that the employment of artillery against porpoises is perfectly useless, that a reward for killing them singly is equally unavailing, and that the only thing to do is to encourage the fishermen to unite in chasing the porpoises, and in forming a mutual insurance guarantee against their depredations. In the meantime the Department of the Marine might continue to indemnify, to a certain extent, the proprietors of any nets that have been very seriously injured.

Electric Car Lamp.

One of the latest novelties in the application of electricity consists of an electric reading lamp, which is being fitted to the carriages on the main line of the Southeastern Railway. It is on the principle of the "put a penny in the slot" automatic machines. The apparatus is situated immediately over the passenger's head, and under the rack, and is contained in a small box 5 inches by 3. The light is of five-candle power, and is obtained by the introduction of a penny at the top of the box, and by a subsequent pressure of a knob, and will last for half an hour, extinguishing itself at the end of that time automatically. If the light be required for an indefinite period, a penny every half an hour will suffice. The light can be extinguished at any moment by means of a second button provided for the purpose. One of the special features of the invention is that, if the instrument is out of order, the penny is not lost, as it is in the present machines. It drops right through, and comes out at the bottom of the box, so that it can be recovered, and the same result happens in the case of any coin other than a penny. Each carriage is fitted with an accumulator which supplies the electricity. This invention, so *Nature* says, will add greatly to the comfort of passengers during night journeys.

Progress of Beet Sugar.

Already more than half the world's sugar is derived from European beet root. Science, chemistry, and mechanical skill have combined to transfer the habitat of a prime necessity of life from the tropics, where only it was supposed it could be produced, into the northern latitudes. Science has shown the way to prepare the soil for it, has overcome all the mechanical problems necessary to the extraction of the sugar, made its cultivation profitable, and given employment to tens of thousands of wage earners, and all this within the last twenty years. The future of this great industry seems almost boundless in its possibilities.—*Tribune, Chicago*.

RECENTLY PATENTED INVENTIONS.

Engineering.

LOCOMOTIVE.—James Des Brisay, Vancouver, B. C., Canada. This locomotive has two high pressure cylinders, both controlled by a rotary valve, a passage from which leads to the smoke box, and a low pressure cylinder to which a passage leads from the rotary valve, with other novel features, designed for the more economical use of steam, and to condense it and return the water of condensation to the boiler if desired.

FEED WATER PURIFIER FOR BOILERS.—Ludwig H. Thielmann, Brunswick, Germany. A pipe is connected with the lower part of the boiler and extends through the furnace or flue to a vessel arranged above the water level of the boiler, another pipe connected with this vessel extending into the water space of the boiler, whereby a circulation is maintained in the vessel or purifier which carries the water upward thereto, deposits the impurities, and returns the water to the boiler.

STEAM GENERATOR.—Doc W. Fletcher, St. Louis, Mo. This is a water heater formed of vertical transverse spaced sections having longitudinally extending interlocking pockets forming zigzag flues, designed to use a minimum amount of fuel with large heater capacity, and provide independent water heaters for each radiator or each section of a building.

Mechanical.

PULLEY.—Nathaniel P. Smith, Memphis, Tenn. This invention covers a combination, with split pulleys, of pivoted and adjustable spider sections constructed with opposite partial hub portions, whereby the pulley may be adjusted to large or small shafts without a bushing, or may be adjusted to run true when the shaft is eccentric, or may be eccentrically fitted if desired.

GAUGE.—Thomas E. Cassidy, Hoosick Falls, N. Y. This is a combination tool capable of quick and easy manipulation for use as a surface, scratch or depth gauge, with clamp and scriber arms which may be used alone as dividers, as a compass, or as inside or outside calipers, and as trammel points.

DECORTICATOR FOR RAMIE, ETC.—Michel J. Leruth, New Orleans, La. This machine has a pair of fluted rollers adapted to crush the stalks and stems, points to receive the crushed fiber, decorticating cylinder with teeth and beater ribs, rotary brushes for cleaning the fiber as it is carried forward by the cylinder, a brush for removing the cleaned fiber cylinder, etc., being designed to efficiently decorticate dry fibrous plants in large quantities.

PLAITING MACHINE.—William B. Jones, administrator of George C. Parker, deceased, Paris, Tenn. A perforated metallic sheet with textile facing piece is secured to an open frame, to the forward edge of which is hinged a metallic frame, the material to be plaited being placed over the textile facing piece and the plaits turned with the ordinary knife, when the frame is thrown over the ironing board, the plaits moistened, and a hot iron passed over them.

RING SPINNING MACHINE.—Ernst Gessner, Aue, Saxony, Germany. This invention relates to spinning machinery with a driven spindle and traveler rotated by the strain of the thread seated on and carried up and down by a ring, the winding being accomplished by the difference in speed between the spindle and the winder lagging behind, the object being to adapt this class of machines to yarns of little strength.

SPINNING MACHINES.—The above inventor has likewise obtained three additional patents on spinning machines, the first referring to spindles with rotary winders rotated similarly to travelers in ring frames, by the tension strain of the thread, for continually spinning and simultaneously winding the thread, an arm carrying the thread guide being pivoted or hinged in the plane of the spindle, to allow of its being rotated round the spindle, and oscillated between the spindle and the outer circle of its rotary motion from the forces of centrifugal action and the tension of the thread; the second patent embracing a winder consisting of an arm or bow carrying the thread guide attached to a socket or disk encircling the spindle below the cop, and capable of being oscillated in its motion round the spindle, the socket-bearing part of the winder being in frictional contact with the spindle—while by the other patent the arm or bow connected with the thread guide has its upper and lower ends held and carried on the spindle above and below the cop, so as to be in frictional contact therewith, the winder being rotated not only by the strain of the thread, but being aided by friction from the spindle, diminishing the tension, and permitting soft or slack twisted yarns of short or poor material to be spun on the bare spindle.

Agricultural.

HAY BINDER.—Ephraim R. Kugler, Kingwood, N. J. This binder consists of a post adapted to be set vertically in the load, and on which wind ropes secured at their ends to the wagon and passing over the load, with a lever for turning and locking the post, so as to wind the ropes, thereby quickly and securely binding the load of hay to the wagon.

STACK FASTENER.—William L. Murdy, Albia, Kan. In carrying out this invention the stack is made longer than it is wide, and stakes are inserted therein in three lines, at the top and sides, a rope being passed through apertures in the outer ends of each line of stakes, and the ends of the ropes brought together at each end of the stack, where a weight is suspended from them.

SOD CUTTER.—Lewis T. Price, Endicott, Washington Ter. The frame of this sod cutter is mounted on wheels, and carries cutting disks, there being means for raising and lowering the frame, and locking it in the position to which it is adjusted, the construction being specially designed for cutting heavy

soil on which "nigger wool grass" grows, with many hard and heavy roots that are hard to cut.

RICE HULLING MACHINE.—Arthur A. Bourgeois, Ariel, La. This machine is made with two corrugated plates facing each other, an agitator extending from one plate up through the hopper, in connection with which a slide or trap is arranged, and one of the corrugated plates being connected with a crank shaft, the machine being simple, cheap, and durable.

Miscellaneous.

SHUTTER FASTENER.—Lewis Whitehouse, Easton, Md. This device has a catch plate combined with a centrally pivoted hook, a rod extending through the wall, and having its inner end passing through an apertured end of the hook, a spiral spring being employed, whereby the shutter fastens automatically when opened and is unfastened from the inside of a room by pressing a knob in the wall at one side of the window.

WIRE TIGHTENER AND SPLICER.—Shapley P. R. Taylor, William T. Sharman, and Joseph L. Jamison, Denison, Texas. This device consists of a disk slotted to form wings, the points of which are bent up out of the plane of the disk, with a perforated stem, and adapted to be rotated to secure it in position, the disks being cheap and light, and left permanently on the wires, where they are applied with a hand lever.

END GATE FOR WAGONS.—Samuel J. Mason, Mead, Neb. This device is made with a flat hinge plate called the gate hinge plate, and a combined re-enforcing and hinge wagon plate extending the full width of the rear end of the wagon, and serving also to protect the rear end of the wagon body from wear, in combination with levers pivoted to the wagon body, and connecting rods pivoted to the gate and to the levers.

LUMBER WAGON.—William and John H. Leonhardt, Baltimore, Md. The main frame of the wagon body has a windlass mechanism, and there is a supplemental frame with movable bearing connected with the windlass mechanism, whereby the body may be extended and adjusted for supporting lumber of different lengths, and its forward end elevated for the ready discharge of lumber at the rear end of the wagon.

FOLDING CRATE.—James W. Brook, Lynchburg, Va. The end sections of this crate are hinged to the bottom, and a hollow ventilating partition is provided, serving to divide and give strength to the box, while eyes or staples are arranged on the inner sides of the end uprights to be connected by hook rods extending diagonally between the front and rear sides, the crate when ready for use presenting the appearance of an ordinary crate with hinged top.

BASKET.—Irwin H. Spelman, Cortland, Ohio. This is a splint basket composed of two series of interwoven splints formed into polygonal shape, and having at the corners re-enforcing splints whose lower ends are interwoven with and placed upon the main splints of the basket body at the lower corners, while the upper ends are extended between the divergent main splints of the basket body to fill the interstices.

COMBINED TABLE AND CHAIR.—Willie O. Whitney, Glens Falls, N. Y. This invention provides an article of furniture which may be used interchangeably as a table or chair, the chair back being adapted to form the table top, and the different adjustments being readily effected.

PADDED HAT.—Jesse H. Moyer, Temple, Texas. This invention provides a strip of fibrous material to be placed between the sweat band and body of the hat, and having hooks projecting from one edge to engage the body of the hat and hold the pad or strip in position, whereby a hat that is too large can readily be made to fit.

DRAPERY TRIMMING.—Paul Gumbinner, New York City. This is a fabric trimming for draping furniture, clothing, etc., and is made of woven fabric, sacks or bags, connected at one end in a series to a suspensory band, and gathered or shirred at their free ends, and provided with pendent tassel ornaments.

CORSET CLASP.—John M. V. Le Beau, New Orleans, La. This clasp consists of two spring steel or elastic busks, a lower fastening device, and a series of upper fastening devices, all of the fastenings being held to the face of the busk, and engaging headed pins or buttons which are fixed to the busk to lock or clasp the corset to the body of the wearer.

TOY.—George W. Nusbaum, Lehigh, Pa. This toy consists of a flanged board with certain points thereon separately marked by different colors, balls or marbles bearing also corresponding designations, and the board having depressions and pockets around its edges, with balls or marbles corresponding to these pockets, the depressions and pens defining the portion of the board to which the different marbles belong, and to which they are to be brought without directly moving them with the fingers.

ICE PITCHER.—Edward Playter, Ottawa, Ontario, Canada. This is a pitcher in which water, milk, etc., may be cooled without the ice being brought in contact therewith, the pitcher being provided with internal sockets, and an ice receptacle being provided with trunnions adapted to be journaled in the sockets, the ice receptacle being readily removable from the pitcher when desired.

APPARATUS FOR DELIVERING COAL, ETC.—Charles S. Schenck, New York City. This is an apparatus more particularly for discharging and conveying materials from vessels to various points, or for use in factories or other structures, an endless belt conveyor discharging into a well or pocket, in combination with a bucket elevator lifting the material from the well, and a chute receiving the material and delivering it to an upper trough in which the conveyor belt works.

CISTERN CLEANER.—William A. Palmer, Plymouth, Mich. This device has a hollow body with an open lower end, to which a plate having

an inwardly opening valve is adjustably hinged, with adjustable legs, and a tube with stopper extending from the upper end of the body, the device being capable of ready manipulation for cleaning a cistern without fouling the water it contains.

BOTTLE STOPPER.—Finley Y. Clark, Saratoga, N. Y. Combined with the stopper head and the bottle head is a bail pivotally mounted at the bottle head to swing above and against the top of the stopper head, to hold the stopper in place, a lifting lever pivotally engaging the stopper head and the bail, the device making a convenient stopper for bottles designed to contain aerated waters or liquids of any kind.

ENFLEURAGE.—Gysbert D. Nellensteijn, Amsterdam, Holland. This invention relates to the treatment of flowers and other substances containing ethereal or volatile oils and aromatic parts, and covers a vacuum process for obtaining therefrom pure perfumes or extracts by a single operation in a cheap, simple, and easy manner.

PLUMB BOB.—John M. Cameron, Philadelphia, Pa. This bob is axially bored, and a point inserted in the bore adapted to be extended or withdrawn, the bob also being provided with a clamp for holding a needle point, and a needle fitted thereto, whereby the point is readily adjustable to adapt it to different kinds of work.

PALLET FOR DRYING BRICK.—Charles T. Fitch, Elizabeth, N. J. Combined with the heads united by horizontal connecting bars is a bench horizontally supported upon the heads and secured to the connecting bars, the invention being an improvement on a former patented invention of the same inventor.

SCIENTIFIC AMERICAN BUILDING EDITION.

SEPTEMBER NUMBER.—(No. 47.)

TABLE OF CONTENTS.

1. Elegant plate in colors of a house recently erected at Easton, Pa., for twelve hundred dollars. Messrs. Munn & Co., architects. Perspective elevation, floor plans, page of details, etc.
2. Plate in colors of a residence recently erected at Natchez, Miss., from plans prepared by Messrs. Munn & Co., architects. Perspective elevation, floor plans, details, etc.
3. A ten thousand dollar residence recently erected at Bridgeport, Conn. Perspective elevation and floor plans.
4. A very attractive cottage for six thousand dollars erected at Jersey City Heights, N. J. Floor plans and perspective elevation.
5. Engraving of the U. S. court house and post office at Savannah, Ga.
6. A house at Woodlands, Sevenoaks.
7. Church of the Angels, Los Angeles, Cal.
8. A cottage recently erected at Jersey City Heights, N. J., at a cost of seven thousand seven hundred dollars. Plans and perspective.
9. A house for five thousand five hundred dollars at Jersey City Heights, N. J. J. C. Markham, architect. Elevations and floor plans.
10. A modern house at Bridgeport, Conn., built at a cost of six thousand six hundred dollars. Plans and perspective elevation.
11. A block of six apartment houses lately erected at Bridgeport, Conn., at a cost of five thousand dollars each. Henry Lambert, architect. Floor plans and perspective elevation.
12. A Queen Anne cottage recently built at Englewood, N. J., at a cost of three thousand dollars. Perspective elevation and floor plans.
13. A dwelling for thirty-five hundred to thirty-eight hundred dollars, recently erected at Bridgeport, Conn. Plans and elevations.
14. Perspective view and plan of the new depot recently erected by the Northern Railroad, at Englewood, N. J.
15. A London fire engine house. Cost six thousand dollars. Elevation and ground plan.
16. Engravings of the royal dairy, Windsor Park. The handsomest and most advanced private dairy in the world.
17. The temple of Marcus Aurelius, at Dugga. Page engraving.
18. Monument to Admiral De Coligny.
19. Miscellaneous Contents: Mohammed II. and his architect.—Building trades associations.—The separate sewer system.—Examine the school buildings.—Experiments with hedges, illustrated with 8 figures.—How creosote affects chimney flues.—Potsdam red sandstone.—Chicago foundations.—The tomb of Alexander the Great.—Large girders.—Large contract for building stone.—Wrought iron fence pickets, illustrated.—Decline in immigration.—House heating boilers, illustrated.—Mental sanitation.—Flooring.—Improved hot water heater, illustrated.—Improved sash pulley, illustrated.—The arch of Aurelius at Tripoli.—Government tests of wood.—New station at Hartford, Conn.

The Scientific American Architects and Builders Edition is issued monthly. \$2.50 a year. Single copies, 25 cents. Forty large quarto pages, equal to about two hundred ordinary book pages; forming, practically, a large and splendid MAGAZINE OF ARCHITECTURE, richly adorned with elegant plates in colors and with fine engravings, illustrating the most interesting examples of Modern Architectural Construction and allied subjects.

The Fullness, Richness, Cheapness, and Convenience of this work have won for it the LARGEST CIRCULATION of any Architectural publication in the world. Sold by all newsdealers.

MUNN & CO., PUBLISHERS,
361 Broadway, New York.

Business and Personal.

The charge for insertion under this head is One Dollar a line for each insertion; about eight words to a line. Advertisements must be received at publication office as early as Thursday morning to appear in next issue.

Air navigating machine.—Capital wanted. Great success. No gas to be used. "J. R.," box 773, New York.

The Little Falls (N. Y.) Water Company in testing all the popular water motors have adopted those made by the Tuerk Hydraulic Power Company. Address No. 12 Cortlandt St., New York.

Wanted.—A young or middle aged man to take charge as foreman in erecting department of machine shop engaged in building stationary and automatic engines in Southern Pennsylvania. Pay, \$18 per week; no lost time, and extra for overtime. Must be familiar with valve motions and know how to set them, and would prefer one who understands the indicator. Permanent employment to a competent, energetic man. Send references and state age. One who has had experience preferred. Intemperate men need not apply. Address, "Foreman," P. O. box 773, New York.

Model steam engine. Cir. free. Edgar Side, Phila., Pa. Guild & Garrison, Brooklyn, N. Y., manufacture steam pumps, vacuum pumps, vacuum apparatus, air pumps, acid blowers, filter press pumps, etc.

For the latest improved diamond prospecting drills, address the M. C. Bullock Mfg. Co., Chicago, Ill.

Presses & Dies. Ferracute Mach. Co., Bridgeton, N. J.

The Holly Manufacturing Co., of Lockport, N. Y., will send their pamphlet, describing water works machinery, and containing reports of tests, on application.

Screw machines, milling machines, and drill presses. E. E. Garvin & Co., Laight and Canal Streets, New York.

Iron, Steel, Copper, and Bronze Drop Forgings of every description. Billings & Spencer Co., Hartford, Conn.

Rubber Belting, all sizes, 77½ per cent from regular list. All kinds of Rubber Goods at low prices. John W. Buckley, 156 South Street, New York.

Steam Hammers, Improved Hydraulic Jacks, and Tube Expanders. R. Dudgeon, 24 Columbia St., New York.

Hoisting Engines, Friction Clutch Pulleys, Cut-off Couplings. The D. Frisbie Co., 112 Liberty St., N. Y.

"How to Keep Boilers Clean." Send your address for free 96 p. book. Jas. C. Hotchkiss, 120 Liberty St., N. Y.

The best Coffee roasters, coolers, stoners, separators, polishers, scourers, glossing apparatus, milling and peaberry machines; also rice and macaroni machinery, are built by The Hungerford Co., Broad and Front Sts., N. Y.

For steel castings of best quality, write the Buffalo Steel Foundry, Buffalo, N. Y.

Split Pulleys at low prices, and of same strength and appearance as Whole Pulleys. Yocom & Son's Shafting Works, Drinker St., Philadelphia, Pa.

Send for new and complete catalogue of Scientific and other Books for sale by Munn & Co., 361 Broadway, New York. Free on application.

Notes & Queries

HINTS TO CORRESPONDENTS.

Names and Address must accompany all letters, or no attention will be paid thereto. This is for our information, and not for publication.

References to former articles or answers should give date of paper and page or number of question. **Inquiries** not answered in reasonable time should be repeated; correspondents will bear in mind that some answers require not a little research, and, though we endeavor to reply to all, either by letter or in this department, each must take his turn.

Special Written Information on matters of personal rather than general interest cannot be expected without remuneration.

Scientific American Supplements referred to may be had at the office. Price 10 cents each.

Books referred to promptly supplied on receipt of price. **Minerals** sent for examination should be distinctly marked or labeled.

(1263) L. R. asks how to make the luminous substances used for match safes, bell push buttons, etc., to make them show in the dark. A. For Balmann's luminous paint we refer you to our SUPPLEMENT, Nos. 229 and 497, which we can send by mail for 10 cents. 2. How to clean a plaster of Paris statue. A. Plaster of Paris casts can be cleaned by careful brushing with a little ground pumice stone or other detergent. Organic spots can sometimes be removed by painting with turpentine and water and exposing to the sun under glass.

(1264) W. G. C. asks: Is there any danger of explosion in a hot water coil in cooking stove, by the pipes becoming choked up with sediment or formation of scale? The water makes very little scale in kettle used for boiling water. A. There is a possibility of the pipe becoming closed where hard water is used, and it may then burn out. There is very little danger with an open boiler. Make the coil longer or larger. 2. Will copper studs placed in coil pipe assist in heating the water? If so, what size and how should they be put in? Pipe is ¾ in. inside and about ¾ in. thick. A. Copper studs will not pay for the trouble of putting in.

(1265) E. S. L. asks if there is any way in which a handle, broken from a cast iron skillet, can again be welded or fastened to the skillet. A. It can be attached by riveting a strap to body and handle. Usually the metal is so hard that this will not pay, on account of the difficulty of drilling.

(1266) W. D. G. writes: I had occasion some time ago to take out some iron rods which had formed a rack over an opening in a flume. The rods had been constantly under water for some years, but were very little rusted except about three inches of the lower end, which was driven into the planks forming the bottom of the flume. Why should they rust more where inclosed in wood (spruce) than above it, when the whole was constantly covered with water? A. Probably there was some acid reaction upon the iron in contact with wood.

(1267) T. S. V. asks: In rolling hot iron or steel, does the elongation of the bar take place at the entering side, or at the exit side of the roll, or elsewhere? Does the metal flow forward or backward? A. The elongation takes place along the surface of contact with the rolls. The rod moves from the rolls with the same velocity as the periphery of the rolls inside of the grooves. It approaches the rolls with less velocity than the speed of the rolls, or the metal flows backward in reference to the speed of the roll surface.

(1268) T. H. K., Jr., asks how brass gas fixtures are brightened and lacquered. I have used nitric acid and then dipped them in water, but just as soon as they are exposed to air they discolor again. A. Have the water clean and *boiling* in two vessels. Dip in one water and then in the next as soon as taken from the nitric acid bath, so that there shall be no traces of acid on the fittings. Dry in boxwood sawdust while hot, and place upon a piece of hot sheet iron over a stove. As soon as all traces of water have left, quickly lacquer with very thin shellac varnish, using a camel's hair brush. You can make the lacquer by dissolving shellac in best alcohol, or you can obtain a lacquer for such purpose from some of the firms whose cards appear in our advertising columns. Do not touch the metal with the fingers before lacquering.

(1269) St. G. J. asks how to make a cheap pump for supplying water to mains with a 12 horse power engine, pump to lift water 40 feet. A. If you have tools for log boring, a log lift pump is probably as cheap as any. They can be made of 5 in. bore with safety as to pressure. If you wish to utilize the whole power of your engine, we suggest a box made by bolting four planks together so as to make a square bore six inches in diameter, in which a square bucket can be operated. The bucket and foot valve should be made of hard wood and leather, with iron or lead weight on top of the valves. A clever carpenter should be able to devise the details. Operate the pump rod, which may also be of wood, by a bell crank lever in the manner of the Cornish pumps.

(1270) S. asks: 1. Is the atmosphere lighter or heavier in damp weather? A. Lighter for a given volume. 2. Is the atmosphere the lightest just after a rain? A. No. 3. Has the atmospheric pressure any effect on the barometer? A. Yes; the barometer has for its object the measurement of this pressure. See Meteorology, by Loomis, mailed by us for \$1.75.

(1271) R. asks how to keep tin from being rough or lumpy on articles plated by the dipping process. Also what temperature molten tin should be kept. A. Put a little clean tallo upon the surface of the melted tin when dipping. Make the tin just hot enough to give a clear, shining surface.

(1272) J. H. B. asks how to melt gold which is amalgamated with quicksilver, so as to pour into moulds in the form of bricks. A. If you undertake to melt the gold amalgam in an open crucible, you will lose the mercury by evaporation. The proper way is to place the mass in a retort, sealed tight with clay, with a pipe leading downward from the top of the retort in a receptacle for the condensed mercury. Heat the retort over a furnace to about 660°, when the mercury distills over into the receptacle. The contents of the retort can be placed in a black lead crucible, melted, and poured into an ingot of gold.

(1273) T. S. asks a formula for making solution for coating small iron castings with copper? A. Such deposits are generally wanting in lasting qualities, since they are too thin to protect the iron from atmospheric influences. Dip the articles in a solution of sulphate of copper $\frac{3}{4}$ oz., sulphuric acid $\frac{3}{4}$ oz., water 1 to 2 gallons, and it will give them a coat of pure copper. If the articles remain a few minutes in the solution, the deposit becomes thick and muddy and does not stand any rubbing. Small articles are sometimes coppered by jerking them about in sawdust impregnated in the above solution further diluted with water.

(1274) "Crescent."—We know of no better way to make snow by an ice machine than by placing coils of pipe on the walls of a room and circulating the brine in the coils. Feed the room with moist air, which will congeal upon the pipes as a light frost; by scraping this off you will have an approach to artificial snow.

(1275) J. M. B. asks: Is pure aluminum as good a conductor of electricity as platinum? A. It is a better conductor. 2. May it be used in the manufacture of electrical instruments instead of platinum? A. It may where it is not exposed to heat or to the action of the spark of the extra current, etc.

(1276) J. S. O. asks whether a good ball batter with the same force in the stroke can knock an easy or slow ball further than he can a swift or hard ball? A. We should say the slow ball would be sent the farthest, and that a ball batted from a state of absolute rest, if that were practicable, would go farther still, equal force being in the bat in each case.

(1277) T. H. R.—We know of no difference between a marine glass and a field glass. The white of a man's eye is a very uncertain test for a field glass. Try the dial of a watch at 500 yards, and see if you can tell the time. Good field glasses single may be had from \$5 to \$10. Double from \$10 to \$15. The ordinary power of the Lick telescope is from 300 to 2,000 times. Divide two miles by these numbers for the distance.

TO INVENTORS.

An experience of forty years, and the preparation of more than one hundred thousand applications for patents at home and abroad, enable us to understand the laws and practice on both continents, and to possess unequalled facilities for procuring patents everywhere. A synopsis of the patent laws of the United States and all foreign countries may be had on application, and persons contemplating the securing of patents, either at home or abroad, are invited to write to this office for prices, which are low, in accordance with the times and our extensive facilities for conducting the business. Address MUNN & CO., office SCIENTIFIC AMERICAN, 361 Broadway, New York.

INDEX OF INVENTIONS

For which Letters Patent of the United States were Granted

August 27, 1889,

AND EACH BEARING THAT DATE.

[See note at end of list about copies of these patents.]

Adding machine, J. H. Schnarrenberger.....	409,710
Agitator and conveyer, combined, V. D. Anderson.....	409,816
Air compressor, H. Davey.....	409,773
Alarm. See Burglar alarm. Knob alarm.	
Aluminum chlorides, purifying, H. Y. Castner.....	409,668
Aniline black, J. Bracewell.....	409,822
Aniline black discharge, J. Bracewell.....	409,819
Artist's field and material case, C. J. Krumbeln.....	409,982
Axle lubricator, A. A. Gregory.....	409,962
Axle nut, carriage, A. E. Herman.....	409,681
Axle, vehicle, A. E. Herman.....	409,680
Axle washer, vehicle, C. C. Jerome.....	409,790
Backband hook, J. A. Elliott.....	410,081
Bag. See Feed bag.	
Bag holder, J. Feess.....	409,946
Baling press, E. P. Jaqua.....	410,102
Baling press, T. Tebow.....	410,046
Bar. See Horseshoe bar.	
Barrel cover, J. Moosbrugger (r).....	11,027
Barrel cover, T. E. Ragland.....	409,803
Batteries, apparatus for charging secondary, W. P. Kookogey.....	410,111
Batteries, containing cell for secondary, C. F. Waldron.....	410,054
Bearing, anti-friction, L. B. Gaylor.....	409,782
Bed lock, C. Whitus.....	410,130
Beer, etc., racking-off apparatus for, J. Johnson.....	409,973
Bellows, double-acting, H. Kohn.....	409,980
Belt, electric, C. Everett.....	409,673
Bending metal bars, machine for, T. F. Krug.....	410,112
Bicycle, C. T. Harvey.....	409,964
Blower for furnaces, C. A. Goyno.....	410,091
Board. See Bosom board. Ironing board.	
Boiler. See Steam boiler.	
Boiler furnace, steam, J. Good.....	409,784
Boilers, means for utilizing radiated heat of, F. H. Butts.....	409,915
Boilers, oil burning apparatus for steam, F. Leadbeater.....	409,846
Bolt, D. M. Motherwell.....	409,696
Bolts, machine for turning tapered, S. M. Vaulchain.....	410,061
Bookbinding, L. Brainerd.....	409,824
Book, black leaf check, T. McDowell.....	410,003
Book, manifold memorandum, W. Bertsch.....	409,768
Boot or shoe sole protector, J. G. Dickson.....	409,938
Bosom board, T. J. Jackson.....	409,684
Bottle stopper, J. H. Christman.....	409,922
Bottle stopper, F. Y. Clark.....	409,924
Bottles, sponge holder for mucilage, J. W. Carter.....	409,770
Box. See Flower box. Money box. Neck wear box.	
Box, M. Benas.....	409,661
Box blocker, C. Gall.....	409,743
Box for tobacco, etc., D. C. Ripley.....	409,804
Box or crate, C. E. Parks.....	409,699
Bracket. See Lamp bracket.	
Brake. See Car brake. Wagon brake.	
Brake adjuster, automatic, E. D. Eames.....	410,079
Brick drying pallet, C. T. Fitch.....	409,948
Brick machine, Leyson & Thomas.....	409,988
Bridge, G. H. Pezram.....	409,700
Bucket bail and lid fastener, combined, Stukes & Reid.....	410,044
Bung, barrel, W. H. Sunday.....	409,713
Bureau, Miles & Scollay.....	409,853
Burglar alarm, E. Carter.....	409,919
Burner. See Stove burner.	
Butter press or printer, J. M. Criley.....	409,734
Button strip, Warren & Ames.....	409,888
Calipers and dividers, M. L. Connett.....	409,828
Camera. See Photographic camera.	
Can. See Creaming can.	
Can nozzle, oil, C. B. Underhill.....	409,811
Cane and camp stool, combined, A. B. Purington.....	410,021
Car bearings, machine for lining railway, G. McCulloch.....	410,002
Car brake, J. W. Hurst.....	409,683
Car coupling, R. J. Edwards.....	410,080
Car coupling, Q. J. Hoke.....	409,967
Car coupling, C. D. Moore.....	409,896
Car coupling, W. T. Sims.....	409,875
Car coupling tool, O. D. Woodruff.....	410,061
Car, dumping, J. H. Gearhart.....	409,954
Car for transmission of specie, G. T. Yost.....	409,894
Car seats, ticket casing for, R. J. Smith.....	409,879
Car wheels, constructing, J. Rigby.....	409,708
Cars, pilot or wheel guard for street, G. H. Bahrs.....	409,901
Cars, safety attachment for railway, R. G. Riera.....	409,707
Cars, safety guard for, C. H. Ohm.....	409,861
Cars, station indicator for railway, E. Verpillier.....	409,812
Carding engines, means for fastening card clothing to the top flats of, E. Tweedale.....	410,048
Carding machine, F. H. Carpenter.....	409,918
Cards, circulars, or other like matter, apparatus for delivering, A. Tabour.....	410,045
Carpet stretcher, Henshaw <i>et al.</i>	409,966
Carriage, child's, T. K. Forman.....	409,677
Carriage spring, G. Langbein.....	409,688
Cart, road, Brabb & Smith.....	409,663
Cart, self-loading, J. C. Keleher.....	409,738
Carving machine, S. F. Moore.....	409,695
Case. See Artist's field and material case.	
Cash carrier apparatus, J. G. Davis.....	409,933
Ceiling, metal, F. G. Caldwell.....	409,916
Centrifugal machines, gearing for driving, J. Laidlaw.....	409,984
Charcoal apparatus, J. Scherffius.....	409,873
Check, service, cash, and pass, G. D. Smith.....	409,877
Chemical reactions, facilitating, H. Bower.....	410,067
Chenille fabric, J. Crabtree.....	409,931
Chimney cowl and ventilator, C. B. Loveless.....	409,990
Chopper. See Cotton chopper.	
Churn, P. Kallen.....	410,103
Churn, E. Michaels.....	409,997
Chute, coke, G. A. Mollhenny.....	410,006
Cigar bunching machine, F. A. Schutz.....	409,807
Cigar machine, M. Greensfelder.....	409,785
Cistern cleaner, W. A. Palmer.....	409,862
Clamp. See Dental bit clamp.	
Clarinet, C. G. Conn.....	410,072
Clasp, S. B. Ferris.....	409,779
Cleaner. See Cistern cleaner. Knife cleaner.	
Clock, electric pendulum, A. L. Parcellle.....	410,013
Clock pendulum, G. P. Reed.....	409,705
Clothes drier, L. R. Studley.....	409,809
Clothes hanger, H. Hennig.....	409,839

Clothes line stretcher, H. Hennig.....	409,840
Clothes pin, J. A. Stewart.....	409,880
Clutch, friction, E. Savoral.....	409,871
Coal cutting machine, J. C. Robertson.....	409,870
Coal discharging and conveying apparatus, C. S. Schenck.....	409,872
Coffin lid fastener, L. E. Woodard.....	410,060
Colter plow, L. Walker.....	410,055
Column, compound fireproof, W. H. Drake.....	409,832
Composition of matter, C. T. Lee.....	409,985
Copying sheet, H. W. Brown.....	409,826
Corn cutting knife, J. P. Wood.....	409,723
Corn husking implement, R. W. Hubbard.....	409,788
Corset fastening, S. S. Williamson.....	410,131
Cotton chopper, A. Chambers.....	409,771
Coupling. See Car coupling. Pipe coupling. Shaft coupling. Thill coupling.	
Creaming can, P. S. Fowler.....	409,951
Crib or cradle, P. Agger.....	409,896
Crusher. See Grinding mill crusher.	
Cuff holder, Eiseman & Kaiser.....	409,833
Cultivators, spring tooth fastener for, E. P. Atherton.....	409,817
Curtain fixture, J. Shinn.....	409,760
Cutter. See Meat cutter. Sod cutter. Stalk cutter.	
Cutting wooden dishes, machine for, D. H. Brenner.....	409,909
Decorticator for ramie, etc., M. J. Leruth.....	409,847
Dental bib clamp, J. D. Ennes.....	410,033
Desk, school, C. B. Towle.....	409,884
Door check, C. H. Dixon.....	409,735
Door check, pneumatic, T. Goodenough.....	409,961
Door hanger, P. H. Murphy.....	409,999
Door, screen and storm, C. Loetscher.....	409,750
Door spring, F. W. Tobey.....	410,047
Drawer, E. J. Brown.....	410,068
Drier. See Clothes drier.	
Drying apparatus, J. F. Gent.....	410,085
Drying machine, Knowles & Proctor.....	410,110
Dummy or motor engine, J. T. Van Gestel.....	410,049
Dumping platform, E. Burns.....	409,913
Dust collector attachment, I. E. Baker.....	409,658
Dye, making orine, R. Greville-Williams.....	410,057
Electrode, secondary battery, C. H. Carter.....	410,136
Electrode, secondary battery, J. F. McLaughlin.....	410,007
Electrode, secondary battery, F. H. Smith.....	410,037
Elevators, speed controlling device for, T. H. Melrose.....	409,995
Emery wheel, R. W. Hardie.....	409,837
Endeourage, G. D. Nellensteyn.....	409,859
Engine. See Rotary engine. Steam engine.	
Engines, automatic lubricator for steam, J. H. Steglist, Jr.....	410,035
Engines, stock or tool holder for direct-acting, G. A. Barth.....	409,659
Extension table, W. Blankner.....	409,662
Extension table, W. H. Burk.....	409,911
Fabric. See Chenille fabric. Twilled woven fabric.	
Farm gate, T. A. Tweedy.....	409,716
Fastening device, M. C. Somborn.....	410,038
Faucet, G. W. Mahlmann.....	409,691
Feed bag, B. T. Harris.....	409,838
Feed water heater, A. De Beaumont.....	410,139
Feed water purifier for boilers, L. H. Thielmann.....	409,832
Fence post, metallic, W. M. Presler.....	410,020
Fence wire holder and stretcher, B. Doud.....	410,077
Fibrous lubricator, J. Williams, Jr.....	409,721
Fifth wheel, vehicle, A. O. & R. N. Clemons, 2d.....	409,733
File or holder, paper, J. B. Brown.....	409,730
Filtering medium, water, J. B. & J. F. Ziegler.....	409,585
Filtration, J. W. Hyatt.....	409,970
Firearm lock, E. L. Pupke.....	409,704
Firearm, magazine, C. P. N. Wetherby.....	409,889
Fire extinguisher, M. Magaldi.....	409,796
Fireplace for burning gaseous fuel, R. Young.....	409,765
Flower box, A. Cleland.....	409,925
Folding machine, C. F. Hintze.....	410,098
Frame. See Hay frame.	
Fruit box head, B. Shunk.....	410,034
Fruit cleaning machine, Phelps & Burdon.....	409,754
Fruit picker, S. Brazee.....	409,907
Fuel, device for feeding fluid, W. B. Wright.....	409,724
Furnace. See Boiler furnace.	
Furnace, E. W. Jones.....	409,792
Furnace grate, G. L. Allen.....	409,657
Gauge. See Recording gauge. Surface, scratch, and depth gauge.	
Gauge knife, F. W. Lowe.....	409,849
Game apparatus, H. S. Kenney.....	409,977
Gas and air mixing machine, L. B. White.....	409,719
Gas, apparatus for the manufacture of, W. T. Stewart.....	409,761
Gas, automatic safety lock for, McClure & Holland.....	410,001
Gas lighter, S. B. Battey.....	409,727
Gate. See Farm gate.	
Gate opening and closing device, swing, W. C. Hooker.....	409,969
Gear cutting machine, Drumheller & North.....	409,776
Generator. See Steam generator.	
Glass. See Opera or field glass.	
Glass panels, making ornamental, Endres & Schoellig.....	409,834
Grain binder, S. D. Maddin.....	409,735
Grain scourer, J. M. Case.....	410,063
Grate for refuse burners, P. Keene.....	410,101
Grease and oil separator, E. H. Murphy.....	409,698
Grinding mill crusher, T. Roberts.....	409,869
Gun and projectile for high explosives, S. H. Emmens.....	409,943
Guns, wind gauge sight for, J. W. Soule.....	410,039
Halter, J. H. Philpott.....	409,867
Hammer, drop, E. Hammesfahr.....	409,836
Handle. See Tool handle.	
Hanger. See Clothes hanger. Door hanger.	
Harness attachment, L. D. Saxton.....	410,029
Harness loop, J. N. Barr.....	409,726
Harness loop press, C. Pelissier.....	410,015
Harrow, M. J. Frank.....	409,933
Harrow, D. McHugh.....	410,004
Harrow disk, J. T. Bell.....	409,818
Harvester attachment, E. Houtz.....	410,100
Harvester, corn, B. B. Leedy.....	409,987
Hay binder, E. R. Kugler.....	409,953
Hay distributor, A. McCollum.....	409,858
Hay frame, stock frame, and spring seat combined, J. T. Woods.....	409,764
Heater. See Feed water heater. Hot air and hot water heater.	
Heel, G. Schmidt.....	410,030
Heel trimming machine, C. W. Glidden.....	410,086 to 410,088, 410,090
Hitching post, A. E. Rider.....	410,025
Hoist operating mechanism, J. S. Ebert.....	409,737
Holder. See Bag holder. Cuff holder. Fence wire holder. Order holder. Pen holder. Shade or globe holder.	
Hoof expander, B. Stewart.....	410,041
Hoof pad, A. D. Hamlin.....	410,093
Hook. See Backband hook.	
Horse detach, C. D. Hill.....	410,097

Horseshoe bar, H. C. Magnusson.....	409,850
Horseshoe nails, machine for forging, D. F. Williams.....	409,890
Hams.....	409,890
Horseshoes, removable calk for, J. Neuss, Sr.....	410,008
Hot air and hot water heater, F. Farquhar <i>et al.</i>	409,740
Hydrant, E. L. Rowe.....	410,026
Indicator. See Thermometric indicator.	
Induction coil, E. Thompson.....	409,714
Induction coil, coin-operated, J. H. Elfeling.....	409,738
Influence machine, R. Voss.....	410,058
Insecticide, Smith & Howard.....	410,036
Iron. See Soldering iron.	
Ironing board and table, D. Fetters.....	409,947
Jack. See Lifting jack.	
Joint. See Lock joint. Rail joint.	
Jug top, A. W. Paull.....	409,864
Knife. See Corn cutting knife. Gauge knife.	
Knife cleaner, H. E. Fowler.....	409,742
Knitted web, narrowed, R. W. Scott.....	410,031
Knitting machine, circular, W. L. & A. T. Cathcart.....	410,071
Knitting machine, circular, H. C. Rightmire.....	410,118
Knitting machine, circular warp, W. Start.....	410,040
Knitting machines, looping attachment for, E. Murby.....	409,836
Knob alarm, door, Stickney & Way.....	409,762
Knockdown table, E. A. & C. P. Cornillie.....	409,930
Ladder, W. G. Sickles.....	409,711
Ladder, fire, W. Winkless.....	409,722
Lamp, F. Rhind.....	409,706
Lamp attachment, C. S. Walker.....	409,887
Lamp bracket, electric, J. S. Merrill.....	409,852
Lamp, central draught, A. W. Paull.....	409,863
Lamp, moderator, or carcel, C. D. Arie.....	409,989
Lamp socket, incandescent electric, J. W. Collier.....	409,929
Lamps, wick raiser for central draught, E. L. Bryant.....	409,910
Lantern for advertising or other purposes, magic, Bruckner & Thornton.....	410,135
Lantern, tubular, J. B. Stetson.....	409,712
Latch, gate, M. M. Moore.....	409,797
Lathe having a supplemental drill spindle, turret, J. Hartness.....	409,786
Leaching tank bark, E. F. Smith.....	409,876
Lifting jack, L. J. Creelius.....	410,074
Lightning arrester, H. Lemp.....	409,689
Liner for machinery, W. V. Fischer.....	409,676
Lock. See Bed lock. Firearm lock. Nut lock.	
Lock joint for beams, R. Wray.....	409,893
Locomotive, J. Des Brisay.....	409,936
Loom for weaving tufted fabrics, A. C. H. Salandrouze.....	410,096
Loom for weaving wire, C. F. Wickwire.....	409,813
Loom heald or heddle, J. Yeaton.....	409,725
Loom shedding mechanism, Hattersley & Hill.....	409,787
Lubricator. See Axle lubricator. Fibrous lubricator.	
Lubricator, R. M. Beck.....	409,660
Mail bag deliverer, A. P. Hauss.....	410,095
Malt mashing device, H. Pietsch.....	410,019
Malt and germinating apparatus, J. F. Gent.....	409,956
Marker, land, I. Ivey.....	409,971
Mattress, J. Blocher.....	410,133
Meat cutter, G. V. Brecht.....	409,908
Merry-go-round, J. R. Applegate.....	409,898
Merry-go-round, D. G. Johnson.....	409,972
Metal, attaching composition of matter to, C. T. Lee.....	409,986
Metal pile or fogot, H. W. Borntraeger.....	410,134

Railway, cable or electric street, Clement & Wat-
riss 409,926
Railway crossing, electric, E. E. Ries 409,756
Railway, electric, S. Z. De Ferranti 409,775
Railway system, pneumatic, M. Bodefeld 409,769
Railway tie, A. C. Nickloy 409,890
Railways, device for depressing cables at the
street crossings of cable, G. H. Wright 410,062
Railways, system of electrical distribution for,
W. J. McElroy 409,752
Railways, underground conduit for electric, E. E.
Ries 409,757
Razor stop, J. R. Torrey 409,715
Recorder. See Speed recorder.
Recording gauge, electric, J. Wills 409,891
Reel. See Yarn reel.
Refractory compounds, producing, Stewart &
Hastings 410,042
Register. See Pool register.
Registering machine, C. W. Fowler 409,950
Regulator. See Scale regulator.
Reversing mechanism, N. A. Otto 410,012
Rheobathometer, H. Flad 409,790
Rice hulling machine, A. A. Bourgeois 409,905
Ring. See Packing ring.
Riveting machine, A. G. Digen 409,939
Rolling flanged beams, Kennedy & Aiken 410,107
Rolling flanged beams, mill for, Kennedy & Aiken 410,106
Roofing sheets, machine for edging, L. H. Bohn 410,066
Roofing tank apparatus, portable, C. Burkelman 409,912
Rotary engine, F. D. Owen 409,800
Rotary engine, Studley & Berry 410,048
Rubber, machine for cleaning refuse, C. Mayer 409,693
Rubber shoe attachment, Van Audall & Dolan 409,717
Rule, calipers, dividers, etc., combined carpen-
ter's, W. A. Delmage 409,934
Ruler, perspective, J. Varley 410,050
Saddles, connecting bar for riding, W. W. Lewis 409,848
Sand blast apparatus, J. E. Mathewson 409,751
Sand screen, P. Drendel 410,078
Sash fastener, E. Reed 410,115
Saw filing machine, W. H. Penrose 409,866
Saw gin, W. L. Ellis 410,082
Saw gummer, J. F. Brower 409,825
Sawmills, power feed mechanism for log car-
riages of, C. F. Thompson 409,883
Saw set, P. Ryan 409,805
Sawing beams, apparatus for hot, C. M. Schwab 410,119
Scale regulator, grain, C. H. Cooley 409,669
Scale regulator, grain, F. H. Richards 410,116
Scourer. See Grain scourer.
Scow, dumping, J. Edwards 409,942
Screen. See Sand screen. Window screen.
Screw machine, metal, Fairfield & Witherell 409,674
Seythe sharpening apparatus, J. E. Parmentier 409,753
Seeder, W. D. Arnett 410,064
Separator. See Grease and oil separator.
Sewing machine, S. O'Connor 410,011
Sewing machine, buttonhole, Bennett & Dowling 409,728
Sewing machine treadle, H. K. House 410,099
Sewing machine tuck marker, F. Henry 409,841
Sewing machines, thread controlled stop mechan-
ism for, A. J. Hart 409,943
Shade or globe holder, B. L. Coe 409,928
Shaft coupling, vehicle, J. A. Chapman 409,732
Shaping machines, dirt guard for, U. Eberhardt 409,911
Signal receiving instrument, electric, S. D. Field 408,675
Smokestack, ventilator, O. R. Kuehne 410,113
Sod cutter, L. T. Price 409,868
Sodawater, etc., apparatus for dispensing, W. Gee 409,945
Soldering iron, J. H. Ferns 410,084
Sole trimming machine, C. W. Glidden 410,089
Spacing or marking wheel, F. C. Vibert 409,718
Speed recorder, F. Richard 410,023
Spindle driving bands, tension regulating device
for, A. Netherwood 409,799
Spinning machine, E. Gessner 409,958
Spinning machine, ring, E. Gessner 409,957
Spinning spindle step, Parker & Esten 410,014
Spoke and felly fastening, H. D. Terrell 409,881
Spool machine, E. P. Brownell 409,665
Spring. See Carriage spring. Door spring. Watch
case spring.

Valve gear for steam hammers, M. B. Kirker 409,845
Valve, steam-actuated, E. A. Marsh 409,851
Valve, steam engine, J. H. Williams 409,720
Vehicle, buckboard, G. B. Hamlin 410,094
Vehicle, electrically propelled, R. N. Allen 409,815
Vehicle gear, J. A. Chapman 409,731
Vehicle running gear, J. H. Harvey 409,965
Velocipede, Schloemer & Hausknecht 409,758
Violin support and garment protector, combined,
F. P. Hoelscher 409,842
Vulcanizer, E. B. Crane 410,073
Wagon brake, W. M. Mason 409,692
Wagon gear, Conrad & Hotz 409,829
Wagon or cart, child's, H. H. Higham 409,682
Wagon standard, N. R. Deppe 409,935
Wall socket plate for building timbers, W. H.
Drake 409,831
Washer. See Axle washer.
Washing machine, Kelsey & Gibson 409,794
Washing machine, J. P. Knisley 410,109
Watch case spring, J. D. Ewing 409,739
Watch case spring, H. R. Gaul 409,745
Watches, hair spring stud for, S. Jenkins 409,789
Water motor, L. R. Witherell 410,132
Water sprinkler, W. S. Kisinger 409,978
Water wheel, L. A. Pelton 409,865
Weighing apparatus, automatic grain or oil, R.
Strain, Jr. 409,888
Weighing machine, grain, Pooley & Parkinson 409,702
Wheel. See Emery wheel. Fifth wheel. Metal-
lic wheel. Spacing or marking wheel. Water
wheel.
Whiffletree, M. M. McKinnon 409,793
Windmill, J. W. Currie 409,932
Windward screen, J. W. Pease 409,801
Wire stitching machine, J. F. Daggett 409,830
Wrench. See Power wrench.
Yarn reel, E. C. Duffy 409,940
Yoke, ox, W. Kidd 409,687

DESIGNS.

Burial case, A. W. Glass 19,286
Dish cover, T. B. Atterbury 19,282, 19,283
Hame, N. Kelsay 19,288
Handle for spoons, etc., J. R. Horton 19,287
Spoon, fork, etc., G. H. Balch 19,284, 19,285
Strap, E. B. Stimpson 19,290, 19,291
Suspenders, back plate for, T. O. Potter 19,289

TRADE MARKS.

Carts, D. M. Sechler Carriage Company 16,968
Coffee, roasted, Indiana Coffee Company 16,962
Corn cure, A. B. Paulus & Co. 16,967
Grapevines, grapevine slips, and grapes, S. Hoyt's
Sons 16,961
Hog and poultry cure, W. Hall Medicine Company 16,960
Lamps or stoves and burners therefor, oil, Wall-
work & Wells 16,965
Liniment for man and beast, J. A. Achard 16,969
Perfumes, S. Palmer 16,964
Underwear, J. Meyer & Co. 16,963
Yeast in powdered form, dry, Charm Manufactur-
ing Company 16,966

A printed copy of the specification and drawing of
any patent in the foregoing list will be furnished from
this office for 25 cents. In ordering please state the
name and number of the patent desired, and remit to
Munn & Co., 361 Broadway, New York.

Canadian Patents may now be obtained by the
inventors for any of the inventions named in the fore-
going list, provided they are simple, at a cost of \$40
each. If complicated the cost will be a little more. For
full instructions address Munn & Co., 361 Broadway,
New York. Other foreign patents may also be obtained.

Advertisements.

Inside Page, each insertion --- 25 cents a line.
Back Page, each insertion --- \$1.00 a line.

The above are charges per agate line—about eight
words per line. This notice shows the width of the line,
and is set in agate type. Engravings may be had ad-
vertisements at the same rate per agate line, by measure-
ment, as the letter press. Advertisements must be
received at publication office as early as Thursday morn-
ing to appear in next issue.

USE ADAMANT WALL PLASTER

It is Hard, Dense, and
Adhesive. Does not check
or crack. It is impervious
to wind, water, and disease
germs. It dries in a few
hours. It can be applied in
any kind of weather. It is
in general use. Licenses
granted for the mixing,
using, and selling. Address
ADAMANT MFG. CO.
71 E. Genesee Street,
Syracuse, N. Y.

Patent Foot Power Machinery

Complete Outfits.
Wood or Metal workers without steam
power can successfully compete with
the large shops by using our New
LABOR SAVING Machinery,
latest and most improved for practical
shop use, also for Industrial Schools,
Home Training, etc. Catalogue free.
Seneca Falls Mfg. Co.
635 Water Street, Seneca Falls, N. Y.

EDISON LAMPS

For Decorative,
Surgical, Dental,
poses. From 1/2
er. From 2 1/2
Catalogue on

EDISON LAMP CO.
Harrison, N. J.

PULLEYS.

Cheapest, Lightest, and Best. Made by
Hardwood Split P. Co., Menasha, Wis.

C&C ELECTRIC MOTORS
FROM 1/2 HORSE POWER UP TO 100
DRIVING LATHES, VENTILATORS,
FANS, SEWING MACHINES, PUMPS,
ELEVATORS, PRINTING PRESSES, ETC.
THESE MOTORS
RUN BY ELECTRIC CURRENT
FROM ARC OR INCANDESCENT
LIGHT CIRCUITS OR STORAGE
BATTERY
THE C&C ELECTRIC MOTOR CO.
414-416 GREENWICH ST. NEW YORK

SEBASTIAN, MAY & CO'S
Improved Screw Cutting
Foot & Power LATHES \$60
Drill Presses, Chucks, Drills,
Dogs, and machinists' and ama-
teurs' outfits. Lathes on trial.
Catalogues mailed on application.
165 W. 2d St., Cincinnati, O.

JOSEPH PRIESTLEY, LL.D., F.R.S.,
and the Discovery of Vital Air—Oxygen Gas.—By Ben-
jamin Ward Richardson, M.D., F.R.S. A biographical
sketch of Priestley, and an account of his work. With
portrait. Contained in SCIENTIFIC AMERICAN SUP-
PLEMENT, No. 696. Price 10 cents. To be had at this
office and from all newsdealers.

TELEMETERS.

Electric Indicating and Recording
THERMOMETERS,
PRESSURE GAGES,
BAROMETERS
HEIGHT OF WATER GAGES. Transmitter.
See article, p. 63, *Sci. Am.*,
August 8, 1889.
Send for manufacturers' catalogue to
Standard Thermometer Co., Peabody, Mass., U.S.

EADS' SHIP RAILWAY.—A LECTURE
by John C. Henderson on the proposed ship railway
across the Isthmus of Tehuantepec, with a discussion of
the advantages of the scheme and of its practicability.
Contained in SCIENTIFIC AMERICAN SUPPLEMENT,
No. 698. Price 10 cents. To be had at this office and
from all newsdealers.

SECTIONAL
INSULATED AIR COVERINGS
FOR
PIPES,
BOILERS, DRUMS,
AND ALL OTHER
HOT & COLD SURFACES.
SHIELDS & BROWN CO.
143 WORTH ST. NEW YORK. 240 & 242 RANDOLPH ST. CHICAGO.

Scientific Book Catalogue

RECENTLY PUBLISHED.
Our new catalogue containing over 100 pages, includ-
ing works on more than fifty different subjects. Will be
mailed free to any address on application.
MUNN & CO., Publishers Scientific American,
361 Broadway, New York.

ASBESTOS
MINERS & MANUFACTURERS.
The ASBESTOS PACKING CO.
169 CONGRESS ST. BOSTON

2 to 40 H. P.
The MOTOR of 19th CENTURY.
Can be used Any Place, to do Any
Work, and by Any One. No Boiler!
No Fire! No Steam! No Ashes!
No Gages! No Engineer! A per-
fectly safe Motor for all places and
purposes. Cost of operation about one
cent an hour to each indicated horse
power. For circulars, etc., address
Charter Gas Engine Co.
Economy, Reliability,
Simplicity, Safety. P. O. Box 148. Sterling, Ill.

HOME-MADE INCUBATOR.—PRACTI-
cal directions for the manufacture of an effective incu-
bator that has been carefully tested and found to per-
form all that may be reasonably expected; with direc-
tions for operating. With 4 figures. Contained in SCI-
ENTIFIC AMERICAN SUPPLEMENT, No. 630. Price 10
cents. To be had at this office and from all newsdealers.

OTTO GAS ENGINES.
Over 25,000 Sold.
Horizontal Otto Gas Engines.
Vertical Otto Gas Engines.
Twin Cylinder Otto Gas Engines.
Combined Otto Gas Engines
and Pumps.
Combined Otto Gas Engines
and Dynamometers.
OTTO GAS ENGINE WORKS,
CHICAGO, PHILADELPHIA.
New York Agency,
18 Vesey Street.

GRAPHOPHONE AND PHONOGRAPH.
An interesting account of the Edison, Bell, and Tain-
tor apparatuses for the mechanical reproduction of speech,
with detailed description of the same. With 11 figures.
Contained in SCIENTIFIC AMERICAN SUPPLEMENT, No.
669. Price 10 cents. To be had at this office and from
all newsdealers.

VAN DUZEN
GAS ENGINE
NO BOILER. NO COAL.
NO ENGINEER.
No Extra WATER RENT
or INSURANCE.
INSTANTLY STARTED.
DURABLE, RELIABLE,
SAFE and ECONOMICAL.
Send for description and prices.
Van Duzen Gas Engine Co.,
63 E. 2d St., CINCINNATI, O.

USEFUL BOOKS.

Manufacturers, Agriculturists, Chemists, Engineers, Me-
chanics, Builders, men of leisure, and professional
men, of all classes, need good books in the line of
their respective callings. Our post office department
permits the transmission of books through the mails
at very small cost. A comprehensive catalogue of
useful books by different authors, on more than fifty
different subjects, has recently been published for
free circulation at the office of this paper. Subjects
classified with names of author. Persons desiring
a copy, have only to ask for it, and it will be mailed
to them. Address,
MUNN & CO., 361 Broadway, New York.

NICKEL PLATING
& POLISHING MATERIALS.
ZUCKER & LEVETT
CHEMICAL CO. NEW YORK U.S.A.

NICKEL ANODES,
NICKEL SALTS,
ROUGES,
COMPOSITION,
BUFFING WHEELS,
ELECTRO & NICKEL
PLATING OUTFITS.

TO BUSINESS MEN.

The value of the SCIENTIFIC AMERICAN as an ad-
vertising medium cannot be overestimated. Its circulation
is many times greater than that of any similar journal
now published. It goes into all the States and Territo-
ries, and is read in all the principal libraries and reading
rooms of the world. A business man wants something
more than to see his advertisement in a printed news-
paper. He wants circulation. This he has when he
advertises in the SCIENTIFIC AMERICAN. And do not
let the advertising agent influence you to substitute
some other paper for the SCIENTIFIC AMERICAN, when
selecting a list of publications in which you decide it is
for your interest to advertise. This is frequently done,
for the reason that the agent gets a larger commission
from the papers having a small circulation than is allow-
ed on the SCIENTIFIC AMERICAN.

For rates see top of first column of this page, or ad-
dress
MUNN & CO., Publishers,
361 Broadway, New York.

CARY & MOEN CO.
STEEL WIRE OF EVERY DESCRIPTION
& STEEL SPRINGS. NEW YORK CITY
234 W. 29. ST.

DRY AIR REFRIGERATING MACHINE.
Description of Hall's improved horizontal dry air refrig-
erator, designed to deliver about 10,000 cubic feet of
cold air per hour, when running at a speed of 100 revolu-
tions per minute, and capable of reducing the tempera-
ture of 90° above to 50° below zero. With five figures,
showing plan and side elevation of the apparatus, and
diagrams illustrative of its performance. Contained in
SCIENTIFIC AMERICAN SUPPLEMENT, No. 638. Price
10 cents. To be had at this office and from all news-
dealers.

THE ARMSTRONG MFG. CO.

BRIDGEPORT, CONN.

WATER, GAS AND STEAM FITTERS' TOOLS.

Stocks and Dies for Pipe, Bolts, and Brass Pipe,
Wrenches, Pipe Vises, Pipe Cutters, etc.
Catalogues sent free on application.

WATCHMAKERS

Send to American Watch Tool Co.,
Waltham, Mass., for price list of Whitecomb
Lathes and for the new Webster-Whitcomb.

THE EIFFEL TOWER.—AN EXCEL-
lent engraving of the Eiffel one thousand-foot-high
tower, which was opened to the public a few days ago,
and which is to form a part of the French Exposition
attractions, may be found, with description, in the SCI-
ENTIFIC AMERICAN SUPPLEMENT, No. 554. To be
had from newsdealers or at this office. Price 10 cents.

CONTRACTORS
WE MAKE THE
LARGEST LINE OF
ROAD GRADERS,
SCRAPERS, PLOWERS,
FOR CONSTRUCTION
OF THE
WORLD.
NEW ERA
Railroad Builder,
Wagon Road Grader,
Wagon Loader, and
Ditching Machine.
It will place an em-
bankment 1000 cubic
yards of earth in 10
hours at a cost of
1 1/2 to 2 1/2 cts. per yd.
CARPENTER ST. & CARROLL AVE. CHICAGO ILL. U.S.A.

OIL WELL SUPPLY CO. Ltd.

91 & 92 WATER STREET,
Pittsburgh, Pa.
Manufacturers of everything needed for
ARTESIAN WELLS
for either Gas, Oil, Water, or Mineral
Tests, Boilers, Engines, Pipe,
Cordage, Drilling Tools, etc.
Illustrated catalogue, price
lists and discount sheets
on request.

ARTESIAN
Wells, Oil and Gas Wells, drilled
by contract to any depth, from 50
to 3000 feet. We also manufacture
and furnish everything required
to drill and complete same. Port-
able Horse Power and Mounted
Steam Drilling Machines for 100 to
600 ft. Send 5 cents for illustrated
catalogue. Pierce Artesian
and Oil Well Supply Co.,
80 Beaver Street, New York.

THE PHONOGRAPH.—A DETAILED
description of the new and improved form of the pho-
nograph just brought out by Edison. With 8 engrav-
ings. Contained in SCIENTIFIC AMERICAN SUPPLE-
MENT, No. 632. Price 10 cents. To be had at this
office and from all newsdealers.

COMPLETE STEAM PUMP
ONLY SEVEN DOLLARS
DEMAND THIS PUMP
OF YOUR
DEALER. OR WRITE
TO US FOR PRICES.
VAN DUZEN'S PATENT
VAN DUZEN & TIFT.
SOLE MAKERS
CINCINNATI, O.

FRESH AND VALUABLE TECHNICAL BOOKS

BRANNT.—The Metallic Alloys. A Practical Guide for the Manufacture of all kinds of Alloys, Amalgams, and Solders used by Metal Workers; together with their Chemical and Physical Properties and their Application in the Arts and the Industries; with an Appendix on the Coloring of Alloys. Translated and edited, chiefly from the German of A. Krupp and Andreas Wildberger, with extensive additions, by Wm. T. Brannt, one of the editors of the Techno-Chemical Receipt Book. Illustrated by 16 engravings. 1mo., 48 pages. \$2.50

A descriptive circular giving the full contents of the above book sent free to any one who will apply.

EDWARDS.—The American Steam Engineer, Theoretical and Practical. With examples of the latest and most approved American practice in the Design and Construction of Steam Engines and Boilers of every description. For the use of Engineers, Machinists, Boiler Makers, and Students. By Emory Edwards, M.E. Illustrated by 77 engravings. In one volume, 12mo. \$2.50

An illustrated circular of this book, 4 pages, 4to, sent free to any address.

BRANNT.—A Practical Treatise on Animal and Vegetable Fats and Oils, comprising both Fixed and Volatile Oils, etc., as well as the Manufacture of Artificial Butter, Lubricants, including Mineral Lubricating Oils, etc., and on Ozokerite, etc. By Wm. T. Brannt. 244 engravings. 730 pages, 8vo. \$7.50

An illustrated circular, 8 pages, quarto, showing the full table of contents of this book, sent free of postage to any one addressing us.

BRANNT.—A Practical Treatise on the Manufacture of Soap and Candles, based upon the most recent Experiences in the Science and Practice. By Wm. T. Brannt. Illustrated by 163 engravings. 677 pages, 8vo. \$7.50

An illustrated circular, 8 pages, 4to, showing contents of this book, will be sent free of postage to any one furnishing his address.

BRANNT-WAHL.—The Techno-Chemical Receipt Book. Containing Several Thousand Receipts, covering the Latest, most important, and most useful Discoveries in Chemical Technology, and their Practical Application in the Arts and the Industries. By W. T. Brannt and W. H. Wahl, Ph.D. 78 engravings, over 500 pages. \$2.00

A circular showing full contents of this book, 32 pages, sent free on application.

OSBORN.—Practical Manual of Minerals, Mines, and Mining. By Prof. H. S. Osborn, LL.D. Illustrated by 171 engravings from original drawings. 367 pages, 8vo. \$4.50

ROSE.—Steam Boilers. A Practical Treatise on Boiler Construction and Examination. For the use of Practical Boiler Makers, Boiler Users, and Inspectors; and embracing in plain figures all the Calculations necessary in Designing and Classifying Steam Boilers. By Joshua Rose. Illustrated. 8vo. \$2.50

SLOANE.—Home Experiments in Science. By T. O'Connor Sloane, E.M., A.M., Ph.D. Illustrated by 91 engravings. 12mo. \$1.50

Illustrated circulars, each 4 pages 4to, showing the full table of contents of the last three named books, sent free on application.

Our New Revised Descriptive Catalogue of Practical and Scientific Books, 84 pages, 8vo., and our Catalogue of Books on Steam and Steam Engines, Mechanics, Machinery, and Dynamical Engineering, and other Catalogues, the whole covering every branch of Science applied to the Arts, sent free and free of postage, to any one in any part of the world who will furnish his address.

HENRY CAREY BAIRD & CO.,
INDUSTRIAL PUBLISHERS, BOOKSELLERS & IMPORTERS
810 Walnut St., Philadelphia, Pa., U. S. A.

ARCHITECTURAL BOOKS.


Useful, Beautiful, and Cheap.

To any person about to erect a dwelling house or stable, either in the country or city, or any builder wishing to examine the latest and best plans for a church, school house, club house, or any other public building of high or low cost, should procure a complete set of the ARCHITECTS' AND BUILDERS' EDITION OF THE SCIENTIFIC AMERICAN.

The information these volumes contain renders the work almost indispensable to the architect and builder, and to persons about to build for themselves they will find the work suggestive and most useful. They contain colored plates of the elevation, plan, and detail drawings of almost every class of building, with specifications and approximate cost.

Seven bound volumes are now ready and may be obtained, by mail, direct from the publishers or from any newsdealer. Price, \$2.00 a volume. Stitched in paper covers. Subscription price, per annum, \$2.50. Address and remit to

MUNN & CO., Publishers,
361 Broadway, New York.



LITTLE GIANT WATER WHEEL
Cheapest and best wheel in the market.
Send for catalogue and price list.
MUNSON BROS., UTICA, N. Y., U. S. A.

THE COPYING PAD.—HOW TO MAKE and how to use; with an engraving. Practical directions how to prepare the gelatine pad, and also the aniline ink by which the copies are made; how to apply the written letter to the pad; how to take off copies of the letter. Contained in SCIENTIFIC AMERICAN SUPPLEMENT, No. 438. Price 10 cents. For sale at this office and by all newsdealers in all parts of the country.

PERFECT NEWSPAPER FILE

The Koch Patent File, for preserving newspapers, Magazines, and pamphlets, has been recently improved and price reduced. Subscribers to the SCIENTIFIC AMERICAN and SCIENTIFIC AMERICAN SUPPLEMENT can be supplied for the low price of \$1.50 by mail, or \$1.25 at the office of this paper. Heavy board sides; inscription "SCIENTIFIC AMERICAN" in gilt. Necessary for every one who wishes to preserve the paper. Address

MUNN & CO., Publishers SCIENTIFIC AMERICAN.

CURE for the DEAF
by Pack's Pat. Improved
CUSHIONED EAR DRUMS.
Whispers heard distinctly.
Comfortable, invisible. Illustrated book & proofs, FREE. Address
or call on F. HISCOX, 853 Broadway, N. Y. Name this paper.

NEW YORK BELTING AND PACKING CO.

JOHN H. CHEEVER, Treas.

15 PARK ROW, New York.

OLDEST and LARGEST Manufacturers in the United States of

VULCANIZED RUBBER FABRICS

For Mechanical Purposes.

RUBBER BELTING,

Packing, Hose,

Vulcanite Emery Wheels, Rubber Mats, Matting & Treads

SALESROOMS:—Philadelphia, 38 Chestnut St.; Boston, 52 Summer St.; Chicago, 151 Lake St.; Minneapolis, 28 South 2d St.; Cincinnati, 161-163 W. Pearl St.; Cleveland, 176 Superior St.; San Francisco, 14 & 15 Main St.; Detroit, 16-24 Woodward Avenue. European Branch, Fickhuben 5 Hamburg (Freihafengebiet), Germany.

ICE-HOUSE AND REFRIGERATOR.

Directions and Dimensions for construction, with one illustration of cold house for preserving fruit from season to season. The air is kept dry and pure throughout the year at a temperature of from 34° to 36°. Contained in SCIENTIFIC AMERICAN SUPPLEMENT No. 116. Price 10 cents. To be had at this office and of all newsdealers.



ICE-HOUSE AND COLD ROOM.—BY R. G. Hatfield. With directions for construction. Four engravings. Contained in SCIENTIFIC AMERICAN SUPPLEMENT, 59. Price 10 cents. To be had at this office and of all newsdealers.



THE PENNA. DIAMOND DRILL & MFG. CO.
BIRDSBORO, PA., Builders of High Class Steam Engines, Diamond Drilling and General Machinery. Flour Mill Rolls Ground and Grooved.

RATS, MICE, or VERMIN
will not pass through it, IN YOUR WALLS or FLOORS. Sample free. WESTERN MINERAL WOOL CO., Cleveland, Ohio.

THE WATER SUPPLY FOR NEW YORK CITY.—A paper by R. D. A. Parrott, discussing the subject of the water supply areas accessible to New York and their availability for use. Contained in SCIENTIFIC AMERICAN SUPPLEMENT, No. 697. Price 10 cents. To be had at this office and from all newsdealers.



PIPE COVERINGS
Made entirely of ASBESTOS.
Absolutely Fire Proof.


CHALMERS-SPENCE CO., FOOT E. 8TH ST., N. Y.
BRANCHES: Phila, 24 Strawberry St. Chicago, 86 E. Lake St. Pittsburg, 414 Lewis Block.

The Paris Exposition--Illustrated.

The SCIENTIFIC AMERICAN SUPPLEMENT will for some months to come contain illustrations of the buildings and the most interesting objects to be seen at the great French Exposition opened at Paris a few days ago. The illustrations which will embellish the SCIENTIFIC AMERICAN SUPPLEMENT will add an interesting and useful feature to the publication, and subscribers to the regular edition of the SCIENTIFIC AMERICAN, who are not patrons of the SCIENTIFIC AMERICAN SUPPLEMENT, are advised to have their name enrolled on the SUPPLEMENT subscription list at once, so as to secure all the illustrated numbers for preservation. Price, \$5 a year, \$2.50 for six months. News agents everywhere receive subscriptions, or remit to the publishers, **MUNN & CO., 361 Broadway, New York.**

WEBSTER

THE BEST INVESTMENT
For the Family, School, or Professional Library.



Has been for many years Standard Authority in the Gov't Printing Office and U. S. Supreme Court. It is Highly Recommended by 38 State Sup'ts of Schools and the leading College Presidents.

Nearly all the School Books published in this country are based upon Webster, as attested by the leading School Book Publishers.

3000 more Words and nearly 2000 more Engravings than any other American Dictionary.

GET THE BEST.

Sold by all Booksellers. Illustrated Pamphlet with specimen pages, etc., sent free.

G. & C. MERRIAM & CO., Pub'rs, Springfield, Mass.

THE BOOKWALTER STEEL AND IRON CO.

Is now prepared to grant licenses under the Bookwalter, Robert, and other patents owned by it. Parties desiring licenses to operate under these patents will please state, in their application, for what purpose they desire using the process, whether for steel castings, for ingots of dead soft steel, for tool steel, or for ordnance purposes.

No. 18 Cortlandt Street, New York.



BATTLE SHIPS, FIRST-CLASS, ALTER-
native designs for.—An interesting article on the proposed designs for English first-class battle ships, with full particulars, giving outlines of a covered and unprotected parts in profile. Contained in SCIENTIFIC AMERICAN SUPPLEMENT, No. 694. Price 10 cents. To be had at this office and from all newsdealers.



2nd MACHINERY
N. Y. Mach'y Depot, Bridge Store 16, Frankfort St., N. Y.

THE HEAT TREATMENT OF STEEL.
—A lecture by Henry M. Howe, delivered in the Sibley College Course. A valuable study of the effects produced upon iron and steel by exposure to certain high temperatures and to certain changes of high temperature. With 16 illustrations. Contained in SCIENTIFIC AMERICAN SUPPLEMENT, No. 692. Price 10 cents. To be had at this office and from all newsdealers.

AUTOMATIC REGISTER




Counts accurately the movements or productions of machinery. Saves labor and time. Send for circular. GEO. E. IVES, 379 State Street, New Haven, Conn.

PIPE COVERINGS

Made entirely of ASBESTOS.
Absolutely Fire Proof.

CHALMERS-SPENCE CO., FOOT E. 8TH ST., N. Y.
BRANCHES: Phila, 24 Strawberry St. Chicago, 86 E. Lake St. Pittsburg, 414 Lewis Block.



ASK-FOR-GRINDING-VALVE
RE-GRINDING-VALVE
COSTS LESS & OUTLASTS ANY COMPOSITION DISK VALVE. VALVES FOR ALL PURPOSES. SIGHT FEED LUBRICATORS OIL & GREASE CUPS. THE LUNKENHEIMER BRASS MFG CO. CINCINNATI, O.

\$10.00 to \$50.00 per night. A light and profitable business. Magic Lanterns and Views of popular subjects. Catalogues on application. Part 1 Optical. 2 Mathematical. 3 Meteorological. 4 Magic Lanterns, etc. L. MANASSE, 88 Madison Street, Chicago, Ill.

VOLNEY W. MASON & CO.,
FRICTION PULLEYS CLUTCHES and ELEVATORS
PROVIDENCE, R. I.

NEW CATALOGUE
OF
A VALUABLE PAPERS
Contained in SCIENTIFIC AMERICAN SUPPLEMENT, sent free of charge to any address.
MUNN & CO., 361 Broadway, New York.

MODERN SMOKING PIPES
H.G. SCHRAMM CAMDEN, N.J.
Excel all others. Send 10c. for a sample.

ELECTRO MOTOR, SIMPLE, HOW TO
make. By G. M. Hopkins.—Description of a small electro motor devised and constructed with a view to assisting amateurs to make a motor which might be driven with advantage by a current derived from a battery, and which would have sufficient power to operate a foot lathe or machine requiring not over one man power. With 11 figures. Contained in SCIENTIFIC AMERICAN SUPPLEMENT, No. 641. Price 10 cents. To be had at this office and from all newsdealers.

AGENTS WANTED
\$75 per month and expenses paid any active man or woman to sell our goods by sample and live at home. Salary paid promptly and expenses in advance. Full particulars and sample case FREE. We mean just what we say. Address Standard Silverware Co., Boston, Mass.

FOR SALE--SPECIAL BARGAIN.

NET CASH P. O. B. IN ALBANY, N. Y.


1 Wright's Patent Cut-off Horizontal Engine, cylinder 12 x 30 in.; 2 drive pulleys with V cut face, 8 ft. diam.; 2 sole leather belts—Underwood patent; 2 receiving V faced pulleys, 48 in. diam., 2 1/2 in. bore.
1 Pitkin Bros. Horizontal Tubular Boiler, 48 in. shell 30 tubes, 3 in. x 14 ft., fitted with Rogers' pat. shaking grate bars; 1 Pitkin Bros. Feed Water Heater; 1 Blake No. 2 Steam Donkey Pump; 1 Harris Plunger Feed Pump with tight and loose pulleys; 1 large Pine, Iron Bound, Tank.
The whole complete, f. o. b., in Albany. \$800
1 Pond's make Engine Lathe, screw cutting, 14 in. swing, 5 ft. bed. \$100
1 Newhaven Tool Co.'s Power Drill Press, table moved by hand lever, nearly new. \$30
1 Complete Set Wood Box Making Machinery. The lot complete. \$150
W. R. & R. Power Single Surface Planing Machine, 2 foot rolls, counter, 4 pulleys; W. R. & R. Power Cross-cut Saw, steel arbor, 3 ft. counter, 3 pulleys; W. R. & R. Power Adjustable Table Top, Cir. Ripping Saw, counter and pulleys; W. R. & R. Power Matching Machine, table 21 x 42 in., counter and pulleys.
Lot 2 1/2 in. Cold Rolled Shafting, iron, good as new; " Drop & Post Hang's, self-feed oil boxes; " Collins' Patent Couplings; " Bore, Large Pulleys, balanced, 12 to 30 in. and 3 to 10 in. face. Half price of new
2 Pair V Pulleys, 32 in. diam., 2 1/2 in. bore. Power Distributing Pulleys, each. \$5.00
EAST NEW YORK SHOE CO.,
Albany, N. Y.

STEEL TYPE for TYPEWRITERS,
Stencils, Steel Stamps, Rubber and Metal Type Wheels.
New York Stencil Works, Mfrs.
100 Nassau Street, New York.



WATER MOTORS.


The most efficient and economical means of obtaining from one-eighth to fifteen horse power and upward. A motor which does the greatest amount of work with the use of the smallest stream of water, specially adapted for running cheaply and efficiently, Printing Presses, Elevators, Church Organs, Coffee Mills, Sewing Machines, Lathes, Dental Contrivances, and in fact, any piece of Mechanism.
Binghamton Hydraulic Power Co., 182 State Street, Binghamton, N. Y.



THE CUSHMAN KEY DRILL CHUCK.
This is an improvement over all other chucks of its class and is fully guaranteed.
DIAM. HOLDS PRICE
No. 1, 2 in. 0 to 1/2 in. \$6.50
No. 2, 2 1/2 in. 1/2 to 3/4 in. 8.00
Sold by the Trade and Manufactured by THE CUSHMAN CHUCK CO., Hartford, Conn.



HODGE'S
Universal Angle Union
PATENTED.
Combining an elbow and union, and can be set at any angle at which it is desired to run the pipe.
Manufacturers & Wholesale Agents,
ROLLSTONE MACHINE CO., 48 Water St., FITCHBURG, MASS.



BARRELS, KEG, Hogshead, AND STAVE MACHINERY.
Over 50 varieties manufactured by
E. & B. HOLMES,
BUFFALO, N. Y.

DRIERS for Grain, Sand, Salt, Wet S.E. Worrell
Feed, Chemicals, etc. Hannibal, Mo.

ELECTRIC TRACTION ON TRAMWAY
and by Accumulators.—An account of some experiments on electric tramways made under the auspices of the Philpott Brothers in Paris, with a description of the car, accumulators, and motor adopted. With 13 figures. Contained in SCIENTIFIC AMERICAN SUPPLEMENT, No. 693. Price 10 cents. To be had at this office and from all newsdealers.

TOOL AGENTS WANTED
in every SHOP in the United States.
Send 10c. for Catalogue. Stationery &c.
THE FINEST OF MECHANICAL TOOLS. A SPECIALTY.
C.B. JAMES, 98 LAKE ST. CHICAGO.

The Scientific American


PUBLICATIONS FOR 1889.

The prices of the different publications in the United States, Canada, and Mexico are as follows:
RATES BY MAIL.
The Scientific American (weekly), one year \$3.00
The Scientific American Supplement (weekly), one year 5.00
The Scientific American, Export Edition (monthly) one year 5.00
The Scientific American, Architects and Builders Edition (monthly), one year 2.50
COMBINED RATES.
The Scientific American and Supplement, \$7.00
The Scientific American and Architects and Builders Edition, 5.00
The Scientific American, Supplement, and Architects and Builders Edition, 9.00
Proportionate Rates for Six Months.
This includes postage, which we pay. Remit by postal or express money order, or draft to order of
MUNN & CO., 361 Broadway, New York.

Advertisements.

Inside Page, each insertion --- 25 cents a line.
Back Page, each insertion --- \$1.00 a line.

The above are charges per agate line—about eight words per line. This notice shows the width of the line, and is set in agate type. Engravings may head advertisements at the same rate per agate line, by measurement, as the letter press. Advertisements must be received at publication office as early as Thursday morning to appear in next issue.



Wheeling is Better than Walking.

Victor Bicycles

Are Better than Any Others.
Catalogue Free.

Overman Wheel Co., Makers,
BOSTON, MASS.

THE ONLY PRACTICAL Low-Priced Typewriter

First-Class, Rapid, Durable, Business
WORLD TYPEWRITER, 44 characters, \$10; 77 characters, \$15.

Catalogue free. Typewriter Dept., POPE MFG. CO.,
Boston, New York, Chicago.



What is more aggravating than leaky valves, whether in House, Office, or Factory? If you wish to avoid annoyance, INSIST on having Jenkins Bros. Valves. Accept no valves as Jenkins Bros. unless stamped with our "Trade Mark" like cut.

JENKINS BROS.

71 John Street, New York.
105 Milk Street, Boston.
21 North 5th Street, Phila.
54 Dearborn Street, Chicago.

PAINT YOUR ROOFS

With Dixon's Silica-Graphite Paint. It will cover two or three times more surface and last four or five times longer than any other paint. Not affected by heat or cold or acids. Send for circular.

JOS. DIXON CRUCIBLE CO., Jersey City, N. J.

JAMES B. EADS.—AN ACCOUNT OF the life and labors of this eminent engineer. With a portrait. Contained in SCIENTIFIC AMERICAN SUPPLEMENT, No. 592. Price 10 cents. To be had at this office and from all newsdealers.

THE KODAK CAMERA

Makes 100 Instantaneous Pictures by simply pressing a button. Anybody can use it who can wind a watch. No focusing. No tripod. Rapid Rectilinear Lens. Photographs moving objects. Can be used indoors.
Division of Labor—Operator can finish his own pictures, or send them to the factory to be finished. Morocco covered Camera, in handsome sole-leather case, loaded for 100 pictures.
For full description of "Kodak" see SCI. AM., Sept. 15, '88. Price, \$25.00. Reloading, \$2.00.

The Eastman Dry Plate & Film Co.
Rochester, N. Y. 115 Oxford St., London.
Send for copy of Kodak Primer with Kodak Photograph.

ESTABLISHED HALF A CENTURY.

MARVIN'S FIRE & BURGLAR SAFES

HAVE MANY PATENTED IMPROVEMENTS NOT FOUND IN OTHER MAKES THAT WILL WELL REPAY AN INVESTIGATION BY THOSE WHO DESIRE TO SECURE THE BEST SAFE
MARVIN SAFE CO.
NEW YORK, PHILADELPHIA, LONDON, ENGLAND.

MALLEABLE AND FINE GRAY IRON ALSO STEEL CASTINGS FROM SPECIAL PATTERNS
THOMAS DEVLIN & CO. FINE TINNING JAPANING AND FINISHING
LEHIGH AVE. & AMERICAN ST. PHILA.

PATENTS.

MESSRS. MUNN & CO., in connection with the publication of the SCIENTIFIC AMERICAN, continue to examine improvements, and to act as Solicitors of Patents for Inventors.
In this line of business they have had forty-two years' experience, and now have unequalled facilities for the preparation of Patent Drawings, Specifications, and the prosecution of Applications for Patents in the United States, Canada, and Foreign Countries. Messrs. Munn & Co. also attend to the preparation of Caveats, Copyrights for Books, Labels, Reissues, Assignments, and Reports on Infringements of Patents. All business entrusted to them is done with special care and promptness, on very reasonable terms.

A pamphlet sent free of charge, on application, containing full information about Patents and how to procure them; directions concerning Labels, Copyrights, Designs, Patents, Appeals, Reissues, Infringements, Assignments, Rejected Cases. Hints on the Sale of Patents, etc.
We also send, free of charge, a Synopsis of Foreign Patent Laws, showing the cost and method of securing patents in all the principal countries of the world.

MUNN & CO., Solicitors of Patents,
361 Broadway, New York.
BRANCH OFFICES.—No. 622 and 624 F Street, Pacific Building, near 7th Street, Washington, D. C.



THE GUTTA PERCHA & RUBBER MFG. CO.

The Largest Manufacturers of Mechanical Rubber Goods in the World.


ESTABLISHED 1855.

Packing, Belting, Hose, Mats, Matting, etc.

35 WARREN STREET, NEW YORK.
Chicago. San Francisco. Portland, Oregon. Boston, Mass.



CELL



ELECTRICAL TUBING



CELL


Composed of Asbestos, combined with water and acid-proof materials, compressed and vulcanized FOR ELECTRICAL PURPOSES.
SWITCH BOARDS, ARMATURE SLEEVES, BATTERY CELLS, INSULATING WASHERS, INSULATING PARTS FOR ARC LIGHTS INCANDESCENT LIGHTS, MOTORS, CHANDELIERS, DYNAMOS, &c.
Special styles and shapes to order. Prices on application.

H. W. JOHNS MANUFACTURING COMPANY,
SOLE MANUFACTURERS OF
H. W. Johns' Asbestos Millboard, Sheathings, Building Felts, Fire-proof Paints, Liquid Paints, Asbestos Roofing, Etc.
87 MAIDEN LANE, NEW YORK. CHICAGO, PHILADELPHIA, LONDON.



**POP SAFETY VALVE
WATER RELIEF VALVE
IMPROVED STEAM GAGE
STEAM ENGINE INDICATOR**

Single Bell Chime Whistle, and all instruments used in connection with Steam Air and Water.
Sole Agents for Clark's Linen Fire Hose.
NEW YORK. LONDON.
CROSBY STEAM GAGE & VALVE CO. 98 Oliver St. Boston, Mass.





**PENBERTHY IMPROVED
AUTOMATIC INJECTOR.**

Why 20,000 have been sold in two years. Because they cost less than others and do equal work. Lift 20 feet and work from head as well. Re-start themselves and require no watching. Will lift through hot pipes, work from 25 to 150 lbs. pressure. Parts removable without disconnecting, also interchangeable. Send for pamphlet.
Penberthy Injector Co., Detroit, Mich.

WORKING MODELS and Experimental Machinery, metal or wood, made to order by MASON & RAUCH, successors to J. F. Werner, 62 Centre Street, New York.

PATENT
JACKET KETTLES,
Plain or Porcelain Lined. Tested to 100 lb. pressure. Send for Lists.
HAND, BURR & CO.
614 and 616 Market St., Philadelphia, Pa.



NATIONAL FILTER.
Special Size to Filter Entire Supply of Water for House.
GUARANTEED TO PRODUCE

BRIGHT SPARKLING WATER

If Filter is Cleaned Once Each Day. Can be Cleaned in 10 Minutes.

LARGE SIZES FOR MILLS AND WATER WORKS.

NATIONAL WATER PURIFYING CO.,
Address for Pamphlet. 145 Broadway or 86 Liberty St., New York.

THE BOOKWALTER CASTING CO.

Are now fully prepared to furnish Steel Castings on short notice, of any size and pattern, made under the **BOOKWALTER AND ROBERT PATENTS.** These castings are guaranteed to be sound and true to the pattern, and of unequalled tensile strength and ductility.
Address **THE BOOKWALTER CASTING CO., Springfield, Ohio.**



CUTLER DESK. BEST IN THE WORLD.
A CUTLER & SON, BUFFALO, N.Y., U.S.A.

THE AMERICAN BELL TELEPHONE CO.

95 MILK ST., BOSTON, MASS.

This Company owns the Letters Patent granted to Alexander Graham Bell, March 7th, 1876, No. 174,465, and January 30th, 1877, No. 186,787.

The transmission of Speech by all known forms of Electric Speaking Telephones infringes the right secured to this Company by the above patents, and renders each individual user of telephones not furnished by it or its licensees responsible for such unlawful use, and all the consequences thereof, and liable to suit therefor.

ANNOUNCEMENT!

Improved methods and special tools make it possible for us to manufacture Elevators, to be operated from line of shafting, at a largely reduced cost.
Purchasers desiring a safe and reliable Elevator, which has stood the test of 37 years' use, should apply to us for an estimate.
All our Elevator machinery is made of the very best materials, and by skilled workmen.
Also manufacturers of Hydraulic Passenger and Freight Elevators.


OTIS BROTHERS & CO.,
38 Park Row, New York.

COPPER TUBES. SHEET BRASS BRASSWIRE
SEND FOR CATALOGUE
125 N. 7th STREET, CHICAGO

BASE BALL.—A DESCRIPTION OF the great national game of the United States, by an English writer, Jno. Newton Crane, with diagram of the field and 7 illustrations of players. Contained in SCIENTIFIC AMERICAN SUPPLEMENT, No. 693. Price 10 cents. To be had at this office and from all newsdealers.

INVENTORS and others desiring new articles manufactured and introduced, address P. O. Box 86, Cleveland, O.

THE INTERNATIONAL CYCLOPEDIA



**SIX REASONS
WHY
YOU SHOULD
BUY IT.**

"It is Up With the Times."—PRESIDENT SEELYE, Smith College, Mass.
"It is Remarkably Accurate."—EDWARD EVERETT HALE, Boston, Mass.
"It is the IDEAL Cyclopaedia."—PROF. JACOBS, Evansville, Wis.
"Its Wide Range of Subjects is of Inestimable Value."—PROF. CHAS. F. SMITH, Vanderbilt University, Tenn.
"It Gives Both Sides of Important Questions and Decides Nothing."—REV. HOWARD CROSBY, New York.
"No One Can Make a Mistake in Purchasing This Work."—PRESIDENT GATES, Iowa College.

Sold for Cash or on our Easy Payment Plan. Delivered Free of Expense. SALESMEN WANTED.
Address Subscription Dept., **DODD, MEAD & COMPANY, Publishers, 753 & 755 Broadway, New York.**

SYRACUSE MALLEABLE IRON WORKS

W B BURNS PROPRIETOR

ELEVATORS OF THE EIFFEL TOWER.
Description of the types of elevators selected for use in the Eiffel tower, with a comparison of the French and American methods. With 10 illustrations. Contained in SCIENTIFIC AMERICAN SUPPLEMENT, No. 695. Price 10 cents. To be had at this office and from all newsdealers.

TO INVENTORS AND MANUFACTURERS

The 58th Annual Exhibition

—OF THE—
American Institute of the City of New York
Will Open **OCTOBER 2, 1889.**

Intending Exhibitors must make early application to secure proper space and classification. For blanks and information, address General Superintendent, American Institute, New York City.


Novelty HOT AIR Furnaces

Expose an Immense Heated Surface.

Extract all the Heat from the Gases. Furnish Pure Warm Air in abundance. Fifteen Years of Test. Universally Satisfactory. Send for "Our Furnace Book."

Abram Cox Stove Co.

MANUFACTURERS,
Philadelphia and New York.



KEY SEATING Machines and 20" Drills.
W. P. DAVIS, Rochester, N. Y.

THE Scientific American

ESTABLISHED 1846.

The Most Popular Scientific Paper in the World.

Only \$3.00 a Year, including Postage. Weekly.
52 Numbers a Year.

This widely circulated and splendidly illustrated paper is published weekly. Every number contains sixteen pages of useful information and a large number of original engravings of new inventions and discoveries, representing Engineering Works, Steam Machinery, New Inventions, Novelties in Mechanics, Manufactures, Chemistry, Electricity, Telegraphy, Photography, Architecture, Agriculture, Horticulture, Natural History, etc. Complete List of Patents each week.

Terms of Subscription.—One copy of the SCIENTIFIC AMERICAN will be sent for one year—52 numbers—postage prepaid, to any subscriber in the United States or Canada, on receipt of three dollars by the publishers; six months, \$1.50; three months, \$1.00.

Clubs.—Special rates for several names, and to Post Masters. Write for particulars.

The safest way to remit is by Postal Order, Draft, or Express Money Order. Money carefully placed inside of envelopes, securely sealed, and correctly addressed, seldom goes astray, but is at the sender's risk. Address all letters and make all orders, drafts, etc., payable to

MUNN & CO.,
361 Broadway, New York.

THE Scientific American Supplement.

This is a separate and distinct publication from THE SCIENTIFIC AMERICAN, but is uniform therewith in size, every number containing sixteen large pages full of engravings, many of which are taken from foreign papers, and accompanied with translated descriptions. THE SCIENTIFIC AMERICAN SUPPLEMENT is published weekly, and includes a very wide range of contents. It presents the most recent papers by eminent writers in all the principal departments of Science and the Useful Arts, embracing Biology, Geology, Mineralogy, Natural History, Geography, Archaeology, Astronomy, Chemistry, Electricity, Light, Heat, Mechanical Engineering, Steam and Railway Engineering, Mining, Ship Building, Marine Engineering, Photography, Technology, Manufacturing Industries, Sanitary Engineering, Agriculture, Horticulture, Domestic Economy, Biography, Medicine, etc. A vast amount of fresh and valuable information obtainable in no other publication.

The most important Engineering Works, Mechanisms, and Manufactures at home and abroad are illustrated and described in the SUPPLEMENT.

Price for the SUPPLEMENT for the United States and Canada, \$5.00 a year, or one copy of the SCIENTIFIC AMERICAN and one copy of the SUPPLEMENT, both mailed for one year for \$7.00. Single copies 10 cents. Address and remit by postal order, express money order, or check.

MUNN & Co., 361 Broadway, N. Y.,
Publishers SCIENTIFIC AMERICAN.

Building Edition.

THE SCIENTIFIC AMERICAN ARCHITECTS' AND BUILDERS' EDITION is issued monthly. \$2.50 a year. Single copies, 25 cents. Forty large quarto pages, equal to about two hundred ordinary book pages; forming a large and splendid Magazine of Architecture, richly adorned with elegant plates in colors, and with other fine engravings; illustrating the most interesting examples of modern Architectural Construction and allied subjects.

A special feature is the presentation in each number of a variety of the latest and best plans for private residences, city and country, including those of very moderate cost as well as the more expensive. Drawings in perspective and in color are given, together with full Plans, Specifications, Sheets of Details, Estimates, etc.

The elegance and cheapness of this magnificent work have won for it the Largest Circulation of any Architectural publication in the world. Sold by all newsdealers. \$2.50 a year. Remit to

MUNN & CO., Publishers,
361 Broadway, New York.

PRINTING INKS.

THE "Scientific American" is printed with CHAS. T. ENRU JOHNSON & CO.'S INK. Tenth and Lombard Sts., Phila., and 47 Rose St., opp. Duane St., N. Y.